SPEC ACCEL™ ACC Result

Copyright 2014-2015 Standard Performance Evaluation Corporation

Cray
(Test Sponsor: Indiana University)

NVIDIA Tesla K20
Cray XK7

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 1.31

ACCEL license: 3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Mar-2015
Hardware Availability: Apr-2013
Software Availability: Feb-2015



Hardware

CPU Name:	AMD Opteron 6276
CPU Characteristics:	AMD Turbo CORE Technology up to 3.2GHz, Turbo CORE off
CPU MHz:	2300
CPU MHz Maximum:	3200
FPU:	Integrated
CPU(s) enabled:	16 cores, 1 chip, 16 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 16 KB D on chip per core
Secondary Cache:	16 MB I+D on chip per chip, 2 MB shared / 2 cores
L3 Cache:	16 MB I+D on chip per chip, 8 MB shared / 8 cores

Continued on next page

Accelerator

Accel Model Name:	Tesla K20
Accel Vendor:	NVIDIA
Accel Name:	NVIDIA Tesla K20
Type of Accel:	GPU
Accel Connection:	PCIe 2.0 16x
Does Accel Use ECC:	yes
Accel Description:	NVIDIA Tesla K20m GPU, 2496 CUDA cores, 706MHz, 5 GB GDDR5 RAM
Accel Driver:	NVIDIA UNIX x86_64 Kernel Module 319.82

SPEC ACCEL ACC Result

Copyright 2014-2015 Standard Performance Evaluation Corporation

Cray
(Test Sponsor: Indiana University)

NVIDIA Tesla K20
Cray XK7

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 1.31

ACCEL license: 3440A
Test sponsor: Indiana University
Tested by: Indiana University

Test date: Mar-2015
Hardware Availability: Apr-2013
Software Availability: Feb-2015

Hardware (Continued)

Other Cache: None
Memory: 32 GB (4 x 8 GB 2Rx4 PC3L-12800R-11, ECC)
Disk Subsystem: None
Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 11 (x86_64), Cray Linux Environment 4.2
SUSE Linux Enterprise Server 11 (x86_64) 2.6.32.59-0.7.1_1.0402.7496-cray_gem_c
Compiler: Cray Compiling Environment 8.3.8
File System: NFSv3 (IBM N5500 NAS) over Gb ethernet
System State: Multi-user, run level 3
Other Software: NVIDIA CUDA 5.5.20

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
303.ostencil	1963	0.0739	**1964**	**0.0738**	1964	0.0738						
304.olbm	132	3.45	**132**	**3.45**	132	3.44						
314.omriq	**573**	**1.67**	572	1.67	573	1.67						
350.md	104	2.42	105	2.41	**104**	**2.41**						
351.palm	324	1.14	325	1.14	**324**	**1.14**						
352.ep	429	1.24	**429**	**1.24**	430	1.23						
353.clvrleaf	247	1.80	**247**	**1.80**	247	1.80						
354.cg	192	2.12	**192**	**2.12**	192	2.12						
355.seismic	180	2.05	**186**	**1.99**	188	1.97						
356.sp	219	1.26	**219**	**1.26**	219	1.26						
357.csp	136	1.99	136	1.99	**136**	**1.99**						
359.miniGhost	200	1.85	201	1.84	**200**	**1.84**						
360.ilbdc	143	2.57	143	2.57	**143**	**2.57**						
363.swim	**115**	**2.00**	115	1.99	115	2.00						
370.bt	**1038**	**0.215**	1038	0.215	1037	0.215						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /N/soft/mason/specaccel-1.0/Docs/sysinfo
$Rev: 6874 $ $Date:: 2013-11-20 #$ 0953404ef7e75a5f9bbb534c6de3f831
running on nid00849 Thu Mar 26 09:06:21 2015

This section contains SUT (System Under Test) info as seen by
```

Continued on next page

Copyright 2014-2015 Standard Performance Evaluation Corporation

Platform Notes (Continued)

```
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/accel/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : AMD Opteron(TM) Processor 6276
      1 "physical id"s (chips)
      16 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 16
      siblings  : 16
      physical 0: cores 0 1 2 3 4 5 6 7
   cache size : 2048 KB

From /proc/meminfo
   MemTotal:       33084584 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

/usr/bin/lsb_release -d
   SUSE Linux Enterprise Server 11 (x86_64)

From /etc/*release* /etc/*version*
   SuSE-release:
      SUSE Linux Enterprise Server 11 (x86_64)
      VERSION = 11
      PATCHLEVEL = 1
   mazama-release:
      Mazama Wed Aug 28 02:06:30 CDT 2013 on hssbld0 by bwdev
      lsb-cray-mazama-7.1.0

uname -a:
   Linux nid00849 2.6.32.59-0.7.1_1.0402.7496-cray_gem_c #1 SMP Thu Jul 10
   19:17:02 UTC 2014 x86_64 x86_64 x86_64 GNU/Linux


SPEC is set to: /N/soft/mason/specaccel-1.0
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /N/soft        dvs   599T  104T  495T  18% /N/soft

Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

(End of data from sysinfo program)
```

Copyright 2014-2015 Standard Performance Evaluation Corporation

Cray
(Test Sponsor: Indiana University)
NVIDIA Tesla K20
Cray XK7

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 1.31

ACCEL license:	3440A	**Test date:**	Mar-2015
Test sponsor:	Indiana University	**Hardware Availability:**	Apr-2013
Tested by:	Indiana University	**Software Availability:**	Feb-2015

General Notes

```
Baseline   C: gcc
     Fortran: f90 -64 -mp -O2
```

Base Compiler Invocation

C benchmarks:
`cc`

Fortran benchmarks:
`ftn`

Benchmarks using both Fortran and C:
`cc ftn`

Base Portability Flags

314.omriq: `-DSPEC_NO_INLINE`
352.ep: `-DSPEC_NO_INLINE`

Base Optimization Flags

C benchmarks:
`-O2 -h pragma=acc -h nopragma=omp -fpic -dynamic`

Fortran benchmarks:
`-O2 -h acc,noomp -em -fpic -dynamic`

Benchmarks using both Fortran and C:
`-O2 -h pragma=acc -h nopragma=omp -fpic -dynamic -h acc,noomp -em`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/accel/flags/flags-advanced.20150303.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/accel/flags/flags-advanced.20150303.xml`

Copyright 2014-2015 Standard Performance Evaluation Corporation

Cray
(Test Sponsor: Indiana University)
NVIDIA Tesla K20
Cray XK7

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 1.31

ACCEL license:	3440A	**Test date:**	Mar-2015
Test sponsor:	Indiana University	**Hardware Availability:**	Apr-2013
Tested by:	Indiana University	**Software Availability:**	Feb-2015

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v1.0.
Report generated on Wed Apr 15 12:15:32 2015 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 15 April 2015.