SPEC ACCEL™ ACC Result

Copyright 2014-2015 Standard Performance Evaluation Corporation

GIGABYTE
(Test Sponsor: Cirrascale Corporation)

FirePro s9150

GIGABYTE MD70-HB0 Motherboard

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 3.60

ACCEL license: 3842
Test sponsor: Cirrascale Corporation
Tested by: PathScale Inc.

Test date: May-2015
Hardware Availability: Sep-2014
Software Availability: Mar-2015



Hardware

CPU Name:	Intel Xeon E5-2637 v3
CPU Characteristics:	Intel Turbo Boost Technology up to 3.70 GHz
CPU MHz:	3500
CPU MHz Maximum:	3700
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	15 MB I+D on chip per chip
Other Cache:	None

Continued on next page

Accelerator

Accel Model Name:	AMD FirePro s9150
Accel Vendor:	AMD
Accel Name:	FirePro s9150
Type of Accel:	GPU
Accel Connection:	PCIe 3.0 16x
Does Accel Use ECC:	No
Accel Description:	GPU set to high performance of sclk: 86100 mclk: 125000. See notes below.
Accel Driver:	AMD ATI Radeon Linux x86_64 Kernel Module 3.19.0+

SPEC ACCEL ACC Result

Copyright 2014-2015 Standard Performance Evaluation Corporation

GIGABYTE
(Test Sponsor: Cirrascale Corporation)

FirePro s9150

GIGABYTE MD70-HB0 Motherboard

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 3.60

ACCEL license: 3842
Test sponsor: Cirrascale Corporation
Tested by: PathScale Inc.

Test date: May-2015
Hardware Availability: Sep-2014
Software Availability: Mar-2015

Hardware (Continued)

Memory: 32 GB (4 x 8 GB 1Rx4 PC4-2133R-15, running at 2133 MHz)
Disk Subsystem: Western Digital Model: WD7500BPKT-00PK4T0 750Gb SATA 7200 rpm
Other Hardware: None

Software

Operating System: CentOS release 6.6 (Final) 4.0.0-rc6PathScale+
Compiler: PathScale ENZO 2015 v6.0
File System: ext4
System State: Run level 3 (add definition here)
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
303.ostencil	31.2	4.64	32.1	4.52	**32.0**	**4.53**						
304.olbm	49.4	9.21	46.8	9.72	**48.7**	**9.34**						
314.omriq	**63.5**	**15.1**	63.4	15.1	63.6	15.0						
350.md	85.2	2.96	84.6	2.98	**84.9**	**2.97**						
351.palm	190	1.94	196	1.89	**192**	**1.93**						
352.ep	**202**	**2.63**	202	2.63	201	2.63						
353.clvrleaf	139	3.20	**136**	**3.28**	135	3.29						
354.cg	**112**	**3.63**	112	3.63	113	3.62						
355.seismic	83.9	4.41	**84.4**	**4.38**	84.5	4.38						
356.sp	81.6	3.38	**80.2**	**3.44**	80.2	3.44						
357.csp	71.1	3.80	**70.1**	**3.85**	69.9	3.86						
359.miniGhost	222	1.66	**203**	**1.81**	203	1.82						
360.ilbdc	**215**	**1.71**	215	1.71	215	1.71						
363.swim	96.2	2.39	95.8	2.40	**95.8**	**2.40**						
370.bt	50.1	4.46	49.7	4.49	**50.0**	**4.46**						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /home/pathscale/ACCEL/Docs/sysinfo
$Rev: 6874 $ $Date:: 2013-11-20 #$ 0953404ef7e75a5f9bbb534c6de3f831
running on Cirrascale Tue May 12 20:05:30 2015

This section contains SUT (System Under Test) info as seen by
```

Continued on next page

Copyright 2014-2015 Standard Performance Evaluation Corporation

Platform Notes (Continued)

```
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/accel/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2637 v3 @ 3.50GHz
      2 "physical id"s (chips)
      16 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 4
      siblings  : 8
      physical 0: cores 0 1 4 5
      physical 1: cores 0 1 4 5
   cache size : 15360 KB

From /proc/meminfo
   MemTotal:       32945984 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

/usr/bin/lsb_release -d
   CentOS release 6.6 (Final)

From /etc/*release* /etc/*version*
   centos-release: CentOS release 6.6 (Final)
   redhat-release: CentOS release 6.6 (Final)
   system-release: CentOS release 6.6 (Final)
   system-release-cpe: cpe:/o:centos:linux:6:GA

uname -a:
   Linux Cirrascale 4.0.0-rc6PathScale+ #8 SMP Fri Apr 3 11:56:23 PDT 2015
   x86_64 x86_64 x86_64 GNU/Linux

run-level 3 May 11 19:01

SPEC is set to: /home/pathscale/ACCEL
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /dev/sda1      ext4   96G   82G  9.2G  90% /
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.

  BIOS GIGABYTE F15 11/28/2014
  Memory:
   4x Kinston 9995589-001.A00G 8 GB 1 rank 2133 MHz
```

Continued on next page

Platform Notes (Continued)

```
    12x NO DIMM NO DIMM

  (End of data from sysinfo program)
```

General Notes

```
ECC disabled by default
GPU Boost mode enabled by setting the device to the following below
high performance mode: "echo high > /sys/class/drm/card0/device/power_dpm_force_performance_level"
The details for high performance mode: cat /sys/kernel/debug/dri/64/radeon_pm_info
uvd    disabled
vce    disabled
power level avg    sclk: 86100 mclk: 125000
The Intel documentation says the CPU can boost to 3700 Mhz, but dmidecode reports Max Speed: 3600 MHz
Kit built system using no case and just mounted on a test bench
```

Base Compiler Invocation

C benchmarks:
`pathcc`

Fortran benchmarks:
`pathf90`

Benchmarks using both Fortran and C:
`pathcc pathf90`

Base Portability Flags

314.omriq: `-std=gnu89`

Base Optimization Flags

C benchmarks:
`-O3 -acc -device=hawaii`

Fortran benchmarks:
`-O3 -acc -device=hawaii`

Benchmarks using both Fortran and C:
`-O3 -acc -device=hawaii`

Copyright 2014-2015 Standard Performance Evaluation Corporation

GIGABYTE
(Test Sponsor: Cirrascale Corporation)

FirePro s9150

GIGABYTE MD70-HB0 Motherboard

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 3.60

ACCEL license:	3842	**Test date:**	May-2015
Test sponsor:	Cirrascale Corporation	**Hardware Availability:**	Sep-2014
Tested by:	PathScale Inc.	**Software Availability:**	Mar-2015

The flags file that was used to format this result can be browsed at
`http://www.spec.org/accel/flags/pathscale2015_flags.20150318.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/accel/flags/pathscale2015_flags.20150318.xml`

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v1.0.
Report generated on Wed Jun 3 13:43:47 2015 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 3 June 2015.