SPEC ACCEL™ ACC Result

Copyright 2014-2015 Standard Performance Evaluation Corporation

Bull
(Test Sponsor: Technische Universitaet Dresden)

NVIDIA Tesla K80
Bull R400

SPECaccel_acc_peak = 2.44

SPECaccel_acc_base = 2.45

ACCEL license: 37A
Test sponsor: Technische Universitaet Dresden
Tested by: Technische Universitaet Dresden

Test date: Oct-2015
Hardware Availability: Jan-2015
Software Availability: May-2015



Hardware

CPU Name:	Intel Xeon E5-2680 v3
CPU Characteristics:	Intel Turbo Boost Technology up to 3.30 GHz
CPU MHz:	2500
CPU MHz Maximum:	3300
FPU:	Integrated
CPU(s) enabled:	24 cores, 2 chips, 12 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None

Continued on next page

Accelerator

Accel Model Name:	Tesla K80
Accel Vendor:	NVIDIA
Accel Name:	NVIDIA Tesla K80
Type of Accel:	GPU
Accel Connection:	PCIe 2.0 16x
Does Accel Use ECC:	yes
Accel Description:	NVIDIA Tesla K80, Kepler GK210, 2496 CUDA cores, 875 MHz 12 GB GDDR5 RAM (Kepler Generation)
Accel Driver:	NVIDIA UNIX x86_64 Kernel Module 346.46

SPEC ACCEL ACC Result

Copyright 2014-2015 Standard Performance Evaluation Corporation

Bull
(Test Sponsor: Technische Universitaet Dresden)

NVIDIA Tesla K80
Bull R400

SPECaccel_acc_peak = 2.44

SPECaccel_acc_base = 2.45

ACCEL license: 37A
Test sponsor: Technische Universitaet Dresden
Tested by: Technische Universitaet Dresden

Test date: Oct-2015
Hardware Availability: Jan-2015
Software Availability: May-2015

Hardware (Continued)

Memory: 64 GB (8 x 8 GB 2Rx8 PC4-2133R-10)
Disk Subsystem: 62 GB SSD
Other Hardware: --

Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)
2.6.32-504.12.2.el6.x86_64
Compiler: PGI Accelerator Server Complete, Release 15.7
File System: ext4
System State: Run Level 3 (Multi-User)
Other Software: NVIDIA Cuda SDK 7.0, driver version 346.46

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
303.ostencil	59.1	2.46	59.1	2.45	**59.1**	**2.45**	**59.2**	**2.45**	59.1	2.45	59.2	2.45
304.olbm	205	2.22	205	2.22	**205**	**2.22**	**205**	**2.22**	205	2.22	205	2.22
314.omriq	400	2.39	**400**	**2.39**	400	2.39	400	2.39	400	2.39	**400**	**2.39**
350.md	115	2.19	115	2.19	**115**	**2.19**	**115**	**2.19**	115	2.19	115	2.19
351.palm	204	1.82	204	1.81	**204**	**1.81**	204	1.81	209	1.77	**205**	**1.80**
352.ep	305	1.74	**305**	**1.74**	305	1.74	**305**	**1.74**	306	1.73	305	1.74
353.clvrleaf	161	2.77	**161**	**2.77**	161	2.77	**161**	**2.77**	161	2.77	161	2.77
354.cg	**139**	**2.94**	139	2.94	139	2.93	**139**	**2.94**	139	2.94	139	2.94
355.seismic	132	2.80	132	2.80	**132**	**2.80**	**132**	**2.80**	132	2.80	132	2.80
356.sp	**135**	**2.05**	135	2.05	135	2.04	**135**	**2.04**	135	2.04	135	2.05
357.csp	138	1.96	**138**	**1.96**	138	1.95	138	1.95	**138**	**1.96**	138	1.96
359.miniGhost	145	2.54	146	2.54	**145**	**2.54**	**145**	**2.54**	145	2.54	145	2.54
360.ilbdc	136	2.69	**136**	**2.69**	136	2.69	136	2.69	**136**	**2.69**	136	2.69
363.swim	**82.4**	**2.79**	82.3	2.80	82.8	2.78	82.9	2.77	**83.2**	**2.76**	83.3	2.76
370.bt	**51.5**	**4.33**	51.5	4.33	51.6	4.33	**51.6**	**4.33**	51.6	4.32	51.5	4.33

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
MultiThreading disabled in BIOS
Sysinfo program /tmp/spec-accel/1.1/Docs/sysinfo
$Rev: 6965 $ $Date:: 2015-04-21 #$ c05a7f14b1b1765e3fe1df68447e8a35
running on taurusi2060 Fri Oct 23 21:24:22 2015

This section contains SUT (System Under Test) info as seen by
```

Continued on next page

Platform Notes (Continued)

```
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/accel/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2680 v3 @ 2.50GHz
      2 "physical id"s (chips)
      24 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 12
      siblings  : 12
      physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13
      physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13
   cache size : 30720 KB

From /proc/meminfo
   MemTotal:       65868116 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

/usr/bin/lsb_release -d
   Red Hat Enterprise Linux Server release 6.4 (Santiago)

From /etc/*release* /etc/*version*
   redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
   system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

uname -a:
   Linux taurusi2060 2.6.32-504.12.2.el6.x86_64 #1 SMP Sun Feb 1 12:14:02 EST
   2015 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Sep 30 16:57

SPEC is set to: /tmp/spec-accel/1.1
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /dev/sda3      ext4   62G  4.2G   55G   8% /tmp

Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

(End of data from sysinfo program)
```

Base Compiler Invocation

C benchmarks:
pgcc

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
pgfortran

Benchmarks using both Fortran and C:
pgcc pgfortran

Base Optimization Flags

C benchmarks:
-V15.9 -fast -acc -ta=tesla:tesla -ta=tesla:cuda7.0 -tp=haswell-64

Fortran benchmarks:
-V15.9 -fast -acc -ta=tesla:tesla -ta=tesla:cuda7.0 -tp=haswell-64

Benchmarks using both Fortran and C:

353.clvrleaf: -V15.9 -fast -acc -ta=tesla:tesla -ta=tesla:cuda7.0 -tp=haswell-64

359.miniGhost: -V15.9 -fast -acc -ta=tesla:tesla -ta=tesla:cuda7.0 -tp=haswell-64 -Mnomain

Peak Compiler Invocation

C benchmarks:
pgcc

Fortran benchmarks:
pgfortran

Benchmarks using both Fortran and C:
pgcc pgfortran

Peak Optimization Flags

C benchmarks:
-V15.9 -fast -acc -ta=tesla:beta -ta=tesla:cuda7.0 -tp=haswell-64

Fortran benchmarks:
-V15.9 -fast -acc -ta=tesla:beta -ta=tesla:cuda7.0 -tp=haswell-64

Continued on next page

Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

353.clvrleaf: `-V15.9 -fast -acc -ta=tesla:beta -ta=tesla:cuda7.0 -tp=haswell-64`

359.miniGhost: `-V15.9 -fast -acc -ta=tesla:beta -ta=tesla:cuda7.0 -tp=haswell-64 -Mnomain`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/accel/flags/pgi2014_flags.20151201.00.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/accel/flags/pgi2014_flags.20151201.00.xml`

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v1.1.
Report generated on Tue Dec 1 10:42:16 2015 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 30 November 2015.