SPEC ACCEL™ ACC Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

Supermicro
(Test Sponsor: NVIDIA Corporation)

Tesla P100-PCIE-16GB
SuperServer 1028GR-TR

SPECaccel_acc_peak = 8.02

SPECaccel_acc_base = 8.02

ACCEL license: 019
Test sponsor: NVIDIA Corporation
Tested by: NVIDIA Corporation

Test date: May-2017
Hardware Availability: Oct-2015
Software Availability: May-2017



Hardware

CPU Name:	Intel Xeon E5-2698 v3
CPU Characteristics:	
CPU MHz:	2300
CPU MHz Maximum:	3600
FPU:	Integrated
CPU(s) enabled:	32 cores, 2 chips, 16 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	40 MB I+D on chip per chip
Other Cache:	None

Continued on next page

Accelerator

Accel Model Name:	Tesla P100
Accel Vendor:	NVIDIA Corporation
Accel Name:	Tesla P100-PCIE-16GB
Type of Accel:	GPU
Accel Connection:	PCIe
Does Accel Use ECC:	Yes
Accel Description:	See Notes
Accel Driver:	NVIDIA UNIX x86_64 Kernel Module 375.20

SPEC ACCEL ACC Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

Supermicro
(Test Sponsor: NVIDIA Corporation)

Tesla P100-PCIE-16GB
SuperServer 1028GR-TR

SPECaccel_acc_peak = 8.02

SPECaccel_acc_base = 8.02

ACCEL license: 019
Test sponsor: NVIDIA Corporation
Tested by: NVIDIA Corporation

Test date: May-2017
Hardware Availability: Oct-2015
Software Availability: May-2017

Hardware (Continued)

Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)
Disk Subsystem: 500 GB Seagate ST9500620NS 7200 RPM SATA
Other Hardware: None

Software

Operating System: CentOS Linux release 7.2.1511 (Core)
3.10.0-327.22.2.el7.x86_64
Compiler: PGI Professional Edition, Release 17.5
File System: xfs
System State: Run level 3 (multi-user)
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
303.ostencil	17.8	8.14	**17.6**	**8.24**	17.6	8.25	17.8	8.14	**17.6**	**8.24**	17.6	8.25
304.olbm	41.5	11.0	**41.6**	**10.9**	41.6	10.9	41.5	11.0	**41.6**	**10.9**	41.6	10.9
314.omriq	118	8.13	**119**	**8.05**	120	8.00	118	8.13	**119**	**8.05**	120	8.00
350.md	22.4	11.3	**22.6**	**11.2**	24.4	10.3	22.4	11.3	**22.6**	**11.2**	24.4	10.3
351.palm	145	2.54	**143**	**2.58**	143	2.59	145	2.54	**143**	**2.58**	143	2.59
352.ep	71.1	7.46	**71.1**	**7.45**	71.1	7.45	71.1	7.46	**71.1**	**7.45**	71.1	7.45
353.clvrleaf	52.1	8.55	52.1	8.54	**52.1**	**8.54**	52.1	8.55	52.1	8.54	**52.1**	**8.54**
354.cg	**43.6**	**9.36**	43.5	9.38	44.1	9.25	**43.6**	**9.36**	43.5	9.38	44.1	9.25
355.seismic	39.8	9.31	**39.8**	**9.31**	39.7	9.31	39.8	9.31	**39.8**	**9.31**	39.7	9.31
356.sp	**34.4**	**8.02**	34.3	8.04	34.4	8.02	**34.4**	**8.02**	34.3	8.04	34.4	8.02
357.csp	30.7	8.80	**31.0**	**8.72**	31.0	8.71	30.7	8.80	**31.0**	**8.72**	31.0	8.71
359.miniGhost	50.7	7.28	50.7	7.28	**50.7**	**7.28**	50.7	7.28	50.7	7.28	**50.7**	**7.28**
360.ilbdc	43.2	8.50	**43.1**	**8.51**	43.1	8.51	43.2	8.50	**43.1**	**8.51**	43.1	8.51
363.swim	56.8	4.05	**56.7**	**4.06**	56.5	4.07	56.8	4.05	**56.7**	**4.06**	56.5	4.07
370.bt	12.4	18.0	12.5	17.9	**12.4**	**17.9**	12.4	18.0	12.5	17.9	**12.4**	**17.9**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Stacksize set to 'unlimited'
```

Platform Notes

```
Sysinfo program /local/home/colgrove/SPECACCEL/Docs/sysinfo
$Rev: 6965 $ $Date:: 2015-04-21 #$ c05a7f14b1b1765e3fe1df68447e8a35
running on hsw8 Mon May  8 15:08:54 2017

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/accel/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2698 v3 @ 2.30GHz
      2 "physical id"s (chips)
      64 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 16
      siblings  : 32
      physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
      physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
   cache size : 40960 KB

From /proc/meminfo
   MemTotal:       264038532 kB
   HugePages_Total:   32768
   Hugepagesize:       2048 kB

/usr/bin/lsb_release -d
   CentOS Linux release 7.2.1511 (Core)

From /etc/*release* /etc/*version*
   centos-release: CentOS Linux release 7.2.1511 (Core)
   centos-release-upstream: Derived from Red Hat Enterprise Linux 7.2 (Source)
   os-release:
      NAME="CentOS Linux"
      VERSION="7 (Core)"
      ID="centos"
      ID_LIKE="rhel fedora"
      VERSION_ID="7"
      PRETTY_NAME="CentOS Linux 7 (Core)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:centos:centos:7"
   redhat-release: CentOS Linux release 7.2.1511 (Core)
   system-release: CentOS Linux release 7.2.1511 (Core)
   system-release-cpe: cpe:/o:centos:centos:7

uname -a:
   Linux hsw8 3.10.0-327.22.2.el7.x86_64 #1 SMP Thu Jun 23 17:05:11 UTC 2016
   x86_64 x86_64 x86_64 GNU/Linux
```

Continued on next page

Copyright 2015-2017 Standard Performance Evaluation Corporation

Platform Notes (Continued)

```
run-level 3 May 8 13:53

SPEC is set to: /local/home/colgrove/SPECACCEL
   Filesystem              Type  Size  Used Avail Use% Mounted on
   /dev/mapper/centos-root xfs   443G   28G  415G   7% /

Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

(End of data from sysinfo program)
 Information from pgaccelinfo

 CUDA Driver Version:           8000
 NVRM version:                  NVIDIA UNIX x86_64 Kernel Module  375.20

 Device Number:                 0
 Device Name:                   Tesla P100-PCIE-16GB
 Device Revision Number:        6.0
 Global Memory Size:            17100439552
 Number of Multiprocessors:     56
 Concurrent Copy and Execution: Yes
 Total Constant Memory:         65536
 Total Shared Memory per Block: 49152
 Registers per Block:           65536
 Warp Size:                     32
 Maximum Threads per Block:     1024
 Maximum Block Dimensions:      1024, 1024, 64
 Maximum Grid Dimensions:       2147483647 x 65535 x 65535
 Maximum Memory Pitch:          2147483647B
 Texture Alignment:             512B
 Clock Rate:                    1328 MHz
 Execution Timeout:             No
 Integrated Device:             No
 Can Map Host Memory:           Yes
 Compute Mode:                  default
 Concurrent Kernels:            Yes
 ECC Enabled:                   Yes
 Memory Clock Rate:             715 MHz
 Memory Bus Width:              4096 bits
 L2 Cache Size:                 4194304 bytes
 Max Threads Per SMP:           2048
 Async Engines:                 2
 Unified Addressing:            Yes
 Managed Memory:                Yes
 PGI Compiler Option:           -ta=tesla:cc60
```

Base Compiler Invocation

C benchmarks:
pgcc

Fortran benchmarks:
pgfortran

Benchmarks using both Fortran and C:
pgcc pgfortran

Base Optimization Flags

C benchmarks:
-fast -Mfprelaxed -acc -ta=tesla:cc60 -ta=tesla:cuda8.0

Fortran benchmarks:
-fast -Mfprelaxed -acc -ta=tesla:cc60 -ta=tesla:cuda8.0

Benchmarks using both Fortran and C:

353.clvrleaf: -fast -Mfprelaxed -acc -ta=tesla:cc60 -ta=tesla:cuda8.0

359.miniGhost: -fast -Mfprelaxed -acc -ta=tesla:cc60 -ta=tesla:cuda8.0 -Mnomain

Peak Optimization Flags

C benchmarks:

303.ostencil: basepeak = yes

304.olbm: basepeak = yes

314.omriq: basepeak = yes

352.ep: basepeak = yes

354.cg: basepeak = yes

357.csp: basepeak = yes

370.bt: basepeak = yes

Fortran benchmarks:

Continued on next page

Peak Optimization Flags (Continued)

350.md: `basepeak = yes`

351.palm: `basepeak = yes`

355.seismic: `basepeak = yes`

356.sp: `basepeak = yes`

360.ilbdc: `basepeak = yes`

363.swim: `basepeak = yes`

Benchmarks using both Fortran and C:

353.clvrleaf: `basepeak = yes`

359.miniGhost: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`https://www.spec.org/accel/flags/pgi2017_flags.20170621.00.html`

You can also download the XML flags source by saving the following link:
`https://www.spec.org/accel/flags/pgi2017_flags.20170621.00.xml`

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v75.
Report generated on Wed Jun 21 17:15:25 2017 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 21 June 2017.