SPEC ACCEL™ ACC Result

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology

NVIDIA Tesla V100S-PCIE-32GB

ThinkSystem SR665

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 14.4

ACCEL license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Apr-2020
Hardware Availability: Jun-2020
Software Availability: Jun-2020



Hardware

CPU Name:	AMD EPYC 7H12
CPU Characteristics:	Turbo up to 3.3 GHz
CPU MHz:	2600
CPU MHz Maximum:	3300
FPU:	Integrated
CPU(s) enabled:	128 cores, 2 chips, 64 cores/chip, 2 threads/core
CPU(s) orderable:	1-2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	256 MB I+D on chip per chip
Other Cache:	None

Continued on next page

Accelerator

Accel Model Name:	NVIDIA Tesla V100S
Accel Vendor:	NVIDIA Corporation
Accel Name:	NVIDIA Tesla V100S-PCIE-32GB
Type of Accel:	GPU
Accel Connection:	PCIe 3.0 16x
Does Accel Use ECC:	Yes
Accel Description:	NVIDIA Tesla V100S-PCIE-32GB
Accel Driver:	NVIDIA UNIX x86_64 Kernel Module 418.39

SPEC ACCEL ACC Result

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology

NVIDIA Tesla V100S-PCIE-32GB

ThinkSystem SR665

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 14.4

ACCEL license: 28
Test sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test date: Apr-2020
Hardware Availability: Jun-2020
Software Availability: Jun-2020

Hardware (Continued)

Memory: 1 TB (16 x 64 GB 2Rx4 PC4-3200AA-R)
Disk Subsystem: 1 x 480 GB 2.5" SSD
Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 15 SP1 4.12.14-195-default
Compiler: PGI Professional Edition, Release 19.9
File System: btrfs
System State: Run level 3
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
303.ostencil	7.49	19.4	7.50	19.3	**7.49**	**19.4**						
304.olbm	28.9	15.7	28.9	15.7	**28.9**	**15.7**						
314.omriq	37.4	25.6	37.6	25.4	**37.5**	**25.5**						
350.md	9.55	26.4	**9.56**	**26.4**	9.58	26.3						
351.palm	**107**	**3.46**	107	3.46	107	3.46						
352.ep	44.8	11.8	44.9	11.8	**44.9**	**11.8**						
353.clvrleaf	30.9	14.4	**30.8**	**14.4**	30.8	14.4						
354.cg	**31.6**	**12.9**	31.3	13.0	31.6	12.9						
355.seismic	21.2	17.4	21.4	17.3	**21.2**	**17.4**						
356.sp	19.2	14.4	**19.2**	**14.4**	19.2	14.4						
357.csp	**17.1**	**15.8**	17.1	15.8	17.1	15.8						
359.miniGhost	27.3	13.5	27.3	13.5	**27.3**	**13.5**						
360.ilbdc	21.8	16.8	**21.8**	**16.8**	21.8	16.8						
363.swim	40.0	5.75	**39.6**	**5.81**	39.5	5.82						
370.bt	7.53	29.6	7.54	29.6	**7.53**	**29.6**						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /home/ACCEL1.3/Docs/sysinfo
$Rev: 6965 $ $Date:: 2015-04-21 #$ c05a7f14b1b1765e3fe1df68447e8a35
running on linux-x8nq Wed Apr 15 13:10:00 2020

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/accel/Docs/config.html#sysinfo
```

Continued on next page

Platform Notes (Continued)

```
From /proc/cpuinfo
   model name : AMD EPYC 7H12 64-Core Processor
      2 "physical id"s (chips)
      128 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 64
      siblings  : 64
      physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
      22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
      47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63
      physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
      22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
      47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63
   cache size : 512 KB

From /proc/meminfo
   MemTotal:       1056689296 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   os-release:
      NAME="SLES"
      VERSION="15-SP1"
      VERSION_ID="15.1"
      PRETTY_NAME="SUSE Linux Enterprise Server 15 SP1"
      ID="sles"
      ID_LIKE="suse"
      ANSI_COLOR="0;32"
      CPE_NAME="cpe:/o:suse:sles:15:sp1"

uname -a:
   Linux linux-x8nq 4.12.14-195-default #1 SMP Tue May 7 10:55:11 UTC 2019
   (8fba516) x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Apr 15 12:46

SPEC is set to: /home/ACCEL1.3
   Filesystem     Type   Size  Used Avail Use% Mounted on
   /dev/sda4      btrfs  444G  160G  284G  37% /home
Additional information from dmidecode:

   Warning: Use caution when you interpret this section. The 'dmidecode' program
   reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to
   hardware, firmware, and the "DMTF SMBIOS" standard.
```

Continued on next page

Platform Notes (Continued)

```
    BIOS Lenovo D8E105F-1.00 03/19/2020
    Memory:
     16x Samsung M393A8G40AB2-CWE 64 kB 2 rank 3200 MT/s
     16x Unknown Unknown

  (End of data from sysinfo program)
```

Base Compiler Invocation

C benchmarks:
pgcc

Fortran benchmarks:
pgfortran

Benchmarks using both Fortran and C:
pgcc pgfortran

Base Optimization Flags

C benchmarks:
-fast -Mfprelaxed -acc -ta=tesla:cc70 -ta=tesla:cuda10.1

Fortran benchmarks:
-fast -Mfprelaxed -acc -ta=tesla:cc70 -ta=tesla:cuda10.1

Benchmarks using both Fortran and C:

353.clvrleaf: -fast -Mfprelaxed -acc -ta=tesla:cc70 -ta=tesla:cuda10.1

359.miniGhost: -fast -Mfprelaxed -acc -ta=tesla:cc70 -ta=tesla:cuda10.1 -Mnomain

The flags file that was used to format this result can be browsed at
https://www.spec.org/accel/flags/pgi_flags.20200506.html

You can also download the XML flags source by saving the following link:
https://www.spec.org/accel/flags/pgi_flags.20200506.xml

Copyright 2015-2020 Standard Performance Evaluation Corporation

Lenovo Global Technology

NVIDIA Tesla V100S-PCIE-32GB

ThinkSystem SR665

SPECaccel_acc_peak = Not Run

SPECaccel_acc_base = 14.4

ACCEL license:	28	**Test date:**	Apr-2020
Test sponsor:	Lenovo Global Technology	**Hardware Availability:**	Jun-2020
Tested by:	Lenovo Global Technology	**Software Availability:**	Jun-2020

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v1.3.
Report generated on Wed May 6 12:04:27 2020 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 6 May 2020.