# SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Lenovo Global Technology

## ThinkSystem SR665 (AMD EPYC 7763)

SPEChpc 2021_tny_base = 31.3

SPEChpc 2021_tny_peak = Not Run

**hpc2021 License:** 28
**Test Sponsor:** Lenovo Global Technology
**Tested by:** Lenovo Global Technology

**Test Date:** Aug-2021
**Hardware Availability:** Mar-2021
**Software Availability:** Oct-2020




## Results Table

| Benchmark | Base | | | | | | | | | Peak | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Model | Ranks | Thrds/Rnk | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Model | Ranks | Thrds/Rnk | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 505.lbm_t | OMP | 96 | 8 | 49.2 | 45.8 | 54.8 | 41.0 | **49.4** | **45.6** | | | | | | | | | |
| 513.soma_t | OMP | 96 | 8 | **87.8** | **42.1** | 88.7 | 41.7 | 85.7 | 43.2 | | | | | | | | | |
| 518.tealeaf_t | OMP | 96 | 8 | **23.5** | **70.1** | 23.4 | 70.4 | 25.7 | 64.3 | | | | | | | | | |
| 519.clvleaf_t | OMP | 96 | 8 | 95.1 | 17.3 | 95.2 | 17.3 | **95.2** | **17.3** | | | | | | | | | |
| 521.miniswp_t | OMP | 96 | 8 | 99.3 | 16.1 | **99.8** | **16.0** | 100 | 16.0 | | | | | | | | | |
| 528.pot3d_t | OMP | 96 | 8 | **87.5** | **24.3** | 87.1 | 24.4 | 87.8 | 24.2 | | | | | | | | | |
| 532.sph_exa_t | OMP | 96 | 8 | 58.4 | 33.4 | 56.9 | 34.3 | **58.3** | **33.4** | | | | | | | | | |
| 534.hpgmgfv_t | OMP | 96 | 8 | 84.3 | 13.9 | 84.8 | 13.8 | **84.4** | **13.9** | | | | | | | | | |
| 535.weather_t | OMP | 96 | 8 | **47.5** | **67.9** | 45.0 | 71.7 | 51.1 | 63.2 | | | | | | | | | |

**SPEChpc 2021_tny_base = 31.3**

**SPEChpc 2021_tny_peak = Not Run**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

# SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Lenovo Global Technology

## ThinkSystem SR665 (AMD EPYC 7763)

SPEChpc 2021_tny_base = 31.3

SPEChpc 2021_tny_peak = Not Run

**hpc2021 License:** 28
**Test Sponsor:** Lenovo Global Technology
**Tested by:** Lenovo Global Technology

**Test Date:** Aug-2021
**Hardware Availability:** Mar-2021
**Software Availability:** Oct-2020

### Hardware Summary

| | |
|---|---|
| Type of System: | Homogenous |
| Compute Node: | ThinkSystem SR665 |
| Interconnect: | Nvidia Mellanox ConnectX-6 HDR |
| File Server Node: | ThinkSystem SR665 |
| Compute Nodes Used: | 6 |
| Total Chips: | 12 |
| Total Cores: | 768 |
| Total Threads: | 768 |
| Total Memory: | 3 TB |
| Max. Peak Threads: | -- |

### Software Summary

| | |
|---|---|
| Compiler: | Intel C/C++/Fortran Compiler 20.4 |
| MPI Library: | Open MPI 4.0.5 |
| Other MPI Info: | -- |
| Other Software: | -- |
| Base Parallel Model: | OMP |
| Base Ranks Run: | 96 |
| Base Threads Run: | 8 |
| Peak Parallel Models: | Not Run |
| Minimum Peak Ranks: | -- |
| Maximum Peak Ranks: | -- |
| Max. Peak Threads: | -- |
| Min. Peak Threads: | -- |

## Node Description: ThinkSystem SR665

### Hardware

| | |
|---|---|
| Number of nodes: | 6 |
| Uses of the node: | Compute |
| Vendor: | Lenovo Global Technology |
| Model: | ThinkSystem SR665 |
| CPU Name: | AMD EPYC 7763 |
| CPU(s) orderable: | 1,2 chips |
| Chips enabled: | 2 |
| Cores enabled: | 128 |
| Cores per chip: | 64 |
| Threads per core: | 1 |
| CPU Characteristics: | Max Boost Clock up to 3.5 GHz |
| CPU MHz: | 2450 |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 512 KB I+D on chip per core |
| L3 Cache: | 256 MB I+D on chip per chip<br>32 MB shared / 8 cores |
| Other Cache: | None |
| Memory: | 512 GB (16 x 32 GB 2Rx8 PC4-3200A-R) |
| Disk Subsystem: | 1 x 480 GB 2.5" SSD |
| Other Hardware: | None |
| Accel Count: | -- |
| Accel Model: | -- |
| Accel Vendor: | -- |
| Accel Type: | -- |
| Accel Connection: | -- |
| Accel ECC enabled: | -- |
| Accel Description: | -- |
| Adapter: | Mellanox ConnectX-6 HDR |
| Number of Adapters: | 1 |
| Slot Type: | PCI-Express 4.0 x16 |
| Data Rate: | 200 Gb/s |
| Ports Used: | 1 |

**(Continued on next page)**

### Software

| | |
|---|---|
| Accelerator Driver: | -- |
| Adapter: | Mellanox ConnectX-6 HDR |
| Adapter Driver: | 5.2-1.0.4 |
| Adapter Firmware: | 20.28.1002 |
| Operating System: | Red Hat Enterprise Linux Server release 8.3,<br>Kernel 4.18.0-193.el8.x86_64 |
| Local File System: | xfs |
| Shared File System: | NFS |
| System State: | Multi-user, run level 3 |
| Other Software: | None |

# SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Lenovo Global Technology

## ThinkSystem SR665 (AMD EPYC 7763)

SPEChpc 2021_tny_base = 31.3

SPEChpc 2021_tny_peak = Not Run

**hpc2021 License:** 28
**Test Sponsor:** Lenovo Global Technology
**Tested by:** Lenovo Global Technology

**Test Date:** Aug-2021
**Hardware Availability:** Mar-2021
**Software Availability:** Oct-2020

## Node Description: ThinkSystem SR665

### Hardware (Continued)

Interconnect Type: Nvidia Mellanox ConnectX-6 HDR

## Node Description: ThinkSystem SR665

### Hardware

| | |
|---|---|
| Number of nodes: | 1 |
| Uses of the node: | Fileserver |
| Vendor: | Lenovo Global Technology |
| Model: | ThinkSystem SR665 |
| CPU Name: | AMD EPYC 7763 |
| CPU(s) orderable: | 1,2 chips |
| Chips enabled: | 2 |
| Cores enabled: | 128 |
| Cores per chip: | 64 |
| Threads per core: | 1 |
| CPU Characteristics: | Max Boost Clock up to 3.5 GHz |
| CPU MHz: | 2450 |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 512 KB I+D on chip per core |
| L3 Cache: | 256 MB I+D on chip per chip<br>32 MB shared / 8 cores |
| Other Cache: | None |
| Memory: | 512 GB (16 x 32 GB 2Rx8 PC4-3200A-R) |
| Disk Subsystem: | 1 x 480 GB 2.5" SSD |
| Other Hardware: | None |
| Accel Count: | -- |
| Accel Model: | -- |
| Accel Vendor: | -- |
| Accel Type: | -- |
| Accel Connection: | -- |
| Accel ECC enabled: | -- |
| Accel Description: | -- |
| Adapter: | Mellanox ConnectX-6 HDR |
| Number of Adapters: | 1 |
| Slot Type: | PCI-Express 4.0 x16 |
| Data Rate: | 200 Gb/s |
| Ports Used: | 1 |
| Interconnect Type: | Nvidia Mellanox ConnectX-6 HDR |

### Software

| | |
|---|---|
| Accelerator Driver: | -- |
| Adapter: | Mellanox ConnectX-6 HDR |
| Adapter Driver: | 5.2-1.0.4 |
| Adapter Firmware: | 20.28.1002 |
| Operating System: | Red Hat Enterprise Linux Server release 8.3 |
| Local File System: | xfs |
| Shared File System: | N/A |
| System State: | Multi-User, run level 3 |
| Other Software: | None |

**Interconnect Description: Nvidia Mellanox ConnectX-6 HDR**

### Hardware

| | |
|---|---|
| Vendor: | Nvidia |
| Model: | Nvidia Mellanox ConnectX-6 HDR |
| Switch Model: | QM8700 Series |
| Number of Switches: | 1 |
| Number of Ports: | 40 |
| Data Rate: | 200 Gb/s |
| Firmware: | 3.9.0606 |
| Topology: | Mesh |
| Primary Use: | MPI Traffic, NFS Access |

### Software

: --

## Submit Notes

```
 The config file option 'submit' was used.
 submit = mpirun ${MPIRUN_OPTS} --allow-run-as-root --oversubscribe
--bind-to numa -map-by numa
-mca coll_hcoll_enable 1 -x HCOLL_ENABLE_NBC=1
-x HCOLL_MAIN_IB=mlx5_0:1 -mca pml ucx
-hostfile /home/HPC2021K35/config/6nodes -npernode 128 -np $ranks $command
```

## General Notes

```
Environment variables set by runhpc before the start of the run:
UCX_MEMTYPE_CACHE = "n"
UCX_TLS = "self,shm,cuda_copy"
```

## Compiler Version Notes

```
==============================================================================
 CC  505.lbm_t(base) 513.soma_t(base) 518.tealeaf_t(base) 521.miniswp_t(base)
     534.hpgmgfv_t(base)
------------------------------------------------------------------------------
Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,
  Version 19.1.3.304 Build 20200925_000000
Copyright (C) 1985-2020 Intel Corporation.  All rights reserved.
icc: NOTE: The evaluation period for this product ends on 11-may-2021 UTC.
------------------------------------------------------------------------------

==============================================================================
 CXXC 532.sph_exa_t(base)
------------------------------------------------------------------------------
Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,
  Version 19.1.3.304 Build 20200925_000000
```

**(Continued on next page)**

## Compiler Version Notes (Continued)

```
Copyright (C) 1985-2020 Intel Corporation.  All rights reserved.
icpc: NOTE: The evaluation period for this product ends on 11-may-2021 UTC.
------------------------------------------------------------------------------

==============================================================================
 FC  519.clvleaf_t(base) 528.pot3d_t(base) 535.weather_t(base)
------------------------------------------------------------------------------
Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)
  64, Version 19.1.3.304 Build 20200925_000000
Copyright (C) 1985-2020 Intel Corporation.  All rights reserved.
ifort: NOTE: The evaluation period for this product ends on 11-may-2021 UTC.
------------------------------------------------------------------------------
```

## Base Compiler Invocation

C benchmarks:
`mpicc`

C++ benchmarks:
`mpicxx`

Fortran benchmarks:
`mpifort`

## Base Portability Flags

513.soma_t: `-DSPEC_NO_VAR_ARRAY_REDUCE`
521.miniswp_t: `-DUSE_KBA -DUSE_ACCELDIR`
532.sph_exa_t: `-DSPEC_USE_LT_IN_KERNELS`

## Base Optimization Flags

C benchmarks:
`-Ofast -no-prec-div -march=core-avx2 -ipo -qopenmp -ansi-alias`

C++ benchmarks:
`-Ofast -no-prec-div -march=core-avx2 -ipo -qopenmp -ansi-alias`

Fortran benchmarks:
`-Ofast -no-prec-div -march=core-avx2 -ipo -qopenmp`

The flags file that was used to format this result can be browsed at
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2021-10-20.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2021-10-20.xml


SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.0.1 on 2018-07-15 17:16:36-0400.
Report generated on 2023-08-25 18:58:22 by hpc2021 PS formatter v1.0.3.
Originally published on 2021-10-20.