



SPEChpc™ 2021 Large Result

Copyright 2021 Standard Performance Evaluation Corporation

Dell Inc.

(Test Sponsor: Texas Advanced Computing Center)


SPEChpc 2021_lrg_base = 17.3

Frontera: PowerEdge C6420 (Intel Xeon Platinum 8280)

SPEChpc 2021_lrg_peak = Not Run

hpc2021 License: 6340
Test Sponsor: Texas Advanced Computing Center
Tested by: Texas Advanced Computing Center

Test Date: Sep-2021
Hardware Availability: Jun-2019
Software Availability: Dec-2020



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
805.lbm_1	OMP	2048	27	145	18.8	148	18.4	143	19.1									
818.tealeaf_1	OMP	2048	27	108	13.4	113	12.8	115	12.6									
819.clvleaf_1	OMP	2048	27	161	13.1	160	13.1	155	13.6									
828.pot3d_1	OMP	2048	27	329	13.8	330	13.8	332	13.7									
834.hpgmgfv_1	OMP	2048	27	168	19.9	173	19.4	171	19.6									
835.weather_1	OMP	2048	27	105	32.5	110	31.1	126	27.2									

SPEChpc 2021_lrg_base = 17.3

SPEChpc 2021_lrg_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Large Result

Copyright 2021 Standard Performance Evaluation Corporation

Dell Inc.

(Test Sponsor: Texas Advanced Computing Center)

SPEChpc 2021_lrg_base = 17.3

Frontera: PowerEdge C6420 (Intel Xeon Platinum 8280)

SPEChpc 2021_lrg_peak = Not Run

hpc2021 License: 6340
Test Sponsor: Texas Advanced Computing Center
Tested by: Texas Advanced Computing Center

Test Date: Sep-2021
Hardware Availability: Jun-2019
Software Availability: Dec-2020

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: PowerEdge C6420
Interconnect: InfiniBand
Compute Nodes Used: 1024
Total Chips: 2048
Total Cores: 57344
Total Threads: 57344
Total Memory: 192 TB
Max. Peak Threads: --

Software Summary

Compiler: C/C++/Fortran: Version 2020 Update 4 of Intel Compilers for Linux
MPI Library: Intel MPI Library 2019 Update 9 for Linux
Other MPI Info: None
Other Software: None
Base Parallel Model: OMP
Base Ranks Run: 2048
Base Threads Run: 27
Peak Parallel Models: Not Run
Minimum Peak Ranks: --
Maximum Peak Ranks: --
Max. Peak Threads: --
Min. Peak Threads: --

Node Description: PowerEdge C6420

Hardware

Number of nodes: 1024
Uses of the node: compute
Vendor: Dell Inc.
Model: PowerEdge C6420
CPU Name: Intel Xeon Platinum 8280
CPU(s) orderable: 1 chips
Chips enabled: 2
Cores enabled: 56
Cores per chip: 28
Threads per core: 1
CPU Characteristics: Turbo up to 4.0 GHz
CPU MHz: 2700
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: 38.5 MB I+D on chip per chip
Other Cache: None
Memory: 192 GB (12 x 16 GB 2Rx8 PC4-2933Y-R)
Disk Subsystem: 1x 240GB SATA SSD
Other Hardware: None
Accel Count: --
Accel Model: --
Accel Vendor: --
Accel Type: --
Accel Connection: --
Accel ECC enabled: --
Accel Description: --
Adapter: NVIDIA ConnectX-6 VPI Infiniband Adapter Card
Number of Adapters: 1
Slot Type: PCIe 3.0 x16
Data Rate: 100Gb/s
Ports Used: 1

Software

Accelerator Driver: --
Adapter: NVIDIA ConnectX-6 VPI Infiniband Adapter Card
Adapter Driver: 5.1-2.5.8.0
Adapter Firmware: 20.25.7020
Operating System: CentOS Linux release 7.8.2003
3.10.0-1127.19.1.el7.x86_64
Local File System: xfs
Shared File System: 10.6 PB Lustre (DDN SFA18K) over Infiniband HDR100
System State: Multi-user, run level 3
Other Software: None

(Continued on next page)



SPEChpc™ 2021 Large Result

Copyright 2021 Standard Performance Evaluation Corporation

Dell Inc.

(Test Sponsor: Texas Advanced Computing Center)

SPEChpc 2021_lrg_base = 17.3

Frontera: PowerEdge C6420 (Intel Xeon Platinum 8280)

SPEChpc 2021_lrg_peak = Not Run

hpc2021 License: 6340
Test Sponsor: Texas Advanced Computing Center
Tested by: Texas Advanced Computing Center

Test Date: Sep-2021
Hardware Availability: Jun-2019
Software Availability: Dec-2020

Node Description: PowerEdge C6420

Hardware (Continued)

Interconnect Type: Infiniband HDR100

Interconnect Description: InfiniBand

Hardware

Vendor: NVIDIA
Model: NVIDIA Infiniband HDR
Switch Model: Quantum CS8500 HDR Modular Switch
Number of Switches: 6
Number of Ports: 600
Data Rate: 200 Gb/s
Firmware: 27.2000.1386
Switch Model: Quantum QM8790 HDR Edge Switch
Number of Switches: 202
Number of Ports: 40
Data Rate: 200 Gb/s
Firmware: 27.2008.2102
Topology: Fat Tree (blocking factor 22:18)
Primary Use: MPI traffic and Lustre access

Software

: --

General Notes

Full HDR connectivity between switches and HDR100 connectivity to the compute nodes. Half of nodes in a rack (44) connect to 22 downlinks of a chassis switch as pairs of HDR100 links into HDR200 ports of the chassis switch. The other 18 ports are uplinks to the six central switches.

Submit Notes

The config file option 'submit' was used.
mpirun -np \$ranks -ppn 2 \$command

General Notes

Environment settings:
ulimit -s unlimited



SPEChpc™ 2021 Large Result

Copyright 2021 Standard Performance Evaluation Corporation

Dell Inc.

(Test Sponsor: Texas Advanced Computing Center)

SPEChpc 2021_lrg_base = 17.3

Frontera: PowerEdge C6420 (Intel Xeon Platinum 8280)

SPEChpc 2021_lrg_peak = Not Run

hpc2021 License: 6340
Test Sponsor: Texas Advanced Computing Center
Tested by: Texas Advanced Computing Center

Test Date: Sep-2021
Hardware Availability: Jun-2019
Software Availability: Dec-2020

Compiler Version Notes

=====
CC 805.lbm_l(base) 818.tealeaf_l(base) 834.hpgmgfv_l(base)
=====

Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,
Version 19.1.3.304 Build 20200925_000000
Copyright (C) 1985-2020 Intel Corporation. All rights reserved.
=====

=====
FC 819.clvleaf_l(base) 828.pot3d_l(base) 835.weather_l(base)
=====

Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)
64, Version 19.1.3.304 Build 20200925_000000
Copyright (C) 1985-2020 Intel Corporation. All rights reserved.
=====

Base Compiler Invocation

C benchmarks:
mpicc

Fortran benchmarks:
mpiifort

Base Portability Flags

805.lbm_l: -std=gnull
818.tealeaf_l: -std=gnull
834.hpgmgfv_l: -std=gnull

Base Optimization Flags

C benchmarks:
-O3 -no-prec-div -fp-model fast=2 -xCORE-AVX512 -ipo -qopenmp
-ansi-alias

Fortran benchmarks:
-O3 -no-prec-div -fp-model fast=2 -xCORE-AVX512 -ipo -qopenmp



SPEChpc™ 2021 Large Result

Copyright 2021 Standard Performance Evaluation Corporation

Dell Inc.

(Test Sponsor: Texas Advanced Computing Center)

SPEChpc 2021_lrg_base = 17.3

Frontera: PowerEdge C6420 (Intel Xeon Platinum 8280)

SPEChpc 2021_lrg_peak = Not Run

hpc2021 License: 6340

Test Sponsor: Texas Advanced Computing Center

Tested by: Texas Advanced Computing Center

Test Date: Sep-2021

Hardware Availability: Jun-2019

Software Availability: Dec-2020

The flags file that was used to format this result can be browsed at

http://www.spec.org/hpc2021/flags/Intel-ic2021-official-linux64_revA.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/hpc2021/flags/Intel-ic2021-official-linux64_revA.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.0.1 on 2021-08-24 10:11:13-0400.

Report generated on 2021-10-20 15:39:27 by hpc2021 PDF formatter v1.0.3.

Originally published on 2021-10-20.