# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 13.2

SPEChpc 2021_sml_peak = 13.9

**hpc2021 License:** 13
**Test Sponsor:** Intel
**Tested by:** Intel

**Test Date:** Jul-2023
**Hardware Availability:** Jan-2023
**Software Availability:** Apr-2023




## Results Table

| Benchmark | Base | | | | | | | | | Peak | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Model | Ranks | Thrds/Rnk | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Model | Ranks | Thrds/Rnk | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 605.lbm_s | OMP | 128 | 14 | **107** | **14.4** | 107 | 14.4 | 107 | 14.5 | OMP | 128 | 14 | **107** | **14.4** | 107 | 14.4 | 107 | 14.5 |
| 613.soma_s | OMP | 128 | 14 | **121** | **13.3** | 120 | 13.3 | 127 | 12.6 | OMP | 32 | 56 | 115 | 13.9 | **112** | **14.2** | 112 | 14.3 |
| 618.tealeaf_s | OMP | 128 | 14 | 262 | 7.83 | **262** | **7.84** | 261 | 7.84 | OMP | 128 | 14 | 251 | 8.17 | **251** | **8.16** | 254 | 8.07 |
| 619.clvleaf_s | OMP | 128 | 14 | 219 | 7.55 | **218** | **7.57** | 218 | 7.58 | OMP | 128 | 14 | 194 | 8.52 | 194 | 8.50 | **194** | **8.50** |
| 621.miniswp_s | OMP | 128 | 14 | 73.4 | 15.0 | 73.9 | 14.9 | **73.8** | **14.9** | OMP | 64 | 28 | 59.3 | 18.5 | **59.7** | **18.4** | 60.0 | 18.3 |
| 628.pot3d_s | OMP | 128 | 14 | **186** | **9.02** | 185 | 9.04 | 186 | 9.02 | OMP | 128 | 14 | **186** | **9.02** | 185 | 9.04 | 186 | 9.02 |
| 632.sph_exa_s | OMP | 128 | 14 | 111 | 20.8 | **111** | **20.7** | 112 | 20.6 | OMP | 896 | 2 | 105 | 21.8 | **109** | **21.1** | 109 | 21.0 |
| 634.hpgmgfv_s | OMP | 128 | 14 | 131 | 7.46 | 131 | 7.44 | **131** | **7.44** | OMP | 896 | 2 | 126 | 7.74 | **129** | **7.55** | 130 | 7.51 |
| 635.weather_s | OMP | 128 | 14 | 48.9 | 53.2 | 50.9 | 51.1 | **49.5** | **52.6** | OMP | 128 | 14 | 48.9 | 53.2 | 50.9 | 51.1 | **49.5** | **52.6** |

**SPEChpc 2021_sml_base = 13.2**

**SPEChpc 2021_sml_peak = 13.9**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 13.2

SPEChpc 2021_sml_peak = 13.9

**hpc2021 License:** 13
**Test Sponsor:** Intel
**Tested by:** Intel

**Test Date:** Jul-2023
**Hardware Availability:** Jan-2023
**Software Availability:** Apr-2023

### Hardware Summary

| | |
|---|---|
| Type of System: | Homogenous Cluster |
| Compute Node: | Intel Server D50DNP2MFALACB (Xeon 8480+) |
| Interconnect: | Mellanox HDR |
| Compute Nodes Used: | 16 |
| Total Chips: | 32 |
| Total Cores: | 1792 |
| Total Threads: | 3584 |
| Total Memory: | 8 TB |
| Max. Peak Threads: | 56 |

### Software Summary

| | |
|---|---|
| Compiler: | Intel oneAPI Compiler 2023.1.0 |
| MPI Library: | Intel MPI Library 2021.9 for Linux OS |
| Other MPI Info: | None |
| Other Software: | None |
| Base Parallel Model: | OMP |
| Base Ranks Run: | 128 |
| Base Threads Run: | 14 |
| Peak Parallel Models: | OMP |
| Minimum Peak Ranks: | 32 |
| Maximum Peak Ranks: | 896 |
| Max. Peak Threads: | 56 |
| Min. Peak Threads: | 2 |

**Node Description: Intel Server D50DNP2MFALACB (Xeon 8480+)**

### Hardware

| | |
|---|---|
| Number of nodes: | 16 |
| Uses of the node: | Compute |
| Vendor: | Intel |
| Model: | Intel Server D50DNP2MFALACB (Xeon 8480+) |
| CPU Name: | Intel Xeon Platinum 8480+ |
| CPU(s) orderable: | 1, 2 chips |
| Chips enabled: | 2 |
| Cores enabled: | 112 |
| Cores per chip: | 56 |
| Threads per core: | 2 |
| CPU Characteristics: | Turbo Boost Technology up to 3.8 GHz |
| CPU MHz: | 2000 |
| Primary Cache: | 32 KB I + 48 KB D on chip per core |
| Secondary Cache: | 2 MB I+D on chip per core |
| L3 Cache: | 105 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 512 GB (16 x 32 GB 2Rx8 PC5-4800B) |
| Disk Subsystem: | 1 x 1 TB NVMe U.2 2.5" SSD |
| Other Hardware: | None |
| Accel Count: | None |
| Accel Model: | None |
| Accel Vendor: | None |
| Accel Type: | None |
| Accel Connection: | None |
| Accel ECC enabled: | None |
| Accel Description: | None |
| Adapter: | Mellanox ConnectX-6 HDR |
| Number of Adapters: | 1 |
| Slot Type: | PCI-Express 4.0 x16 |
| Data Rate: | 200Gbit/s |
| Ports Used: | 1 |
| Interconnect Type: | Mellanox HDR |

### Software

| | |
|---|---|
| Accelerator Driver: | None |
| Adapter: | Mellanox ConnectX-6 HDR |
| Adapter Driver: | 5.9-0.5.5 |
| Adapter Firmware: | 20.36.1010 |
| Operating System: | Rocky Linux 8.7 (Green Obsidian)<br>4.18.0-372.32.1.el8_6.crt3.x86_64 |
| Local File System: | NFS |
| Shared File System: | PANASAS FS |
| System State: | Multi-user |
| Other Software: | None |

## Interconnect Description: Mellanox HDR

### Hardware

| | |
|---|---|
| Vendor: | Mellanox |
| Model: | Mellanox HDR |
| Switch Model: | Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch |
| Number of Switches: | 18 |
| Number of Ports: | 40 |
| Data Rate: | 200 Gbit/s |
| Firmware: | 20.36.1010 |
| Topology: | Fat-tree |
| Primary Use: | MPI Traffic |

### Software

: --

## Submit Notes

```
The config file option 'submit' was used.
```

## General Notes

```
The PANASAS filesystem as described on this result page was formerly
generally available.  At the time of this publication, it may
not be shipping, and/or may not be supported, and/or may fail
to meet other tests of General Availability described in the
SPEC HPG Policy document, http://www.spec.org/hpg/policy.html
```

## Compiler Version Notes

```
==============================================================================
 CXXC 632.sph_exa_s(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
  /global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm
Configuration file:
  /global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/../bin/icpx.cfg
------------------------------------------------------------------------------

==============================================================================
 CC  605.lbm_s(base, peak) 613.soma_s(base, peak) 618.tealeaf_s(base)
      621.miniswp_s(base) 634.hpgmgfv_s(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)
Target: x86_64-unknown-linux-gnu
```

**(Continued on next page)**

## Compiler Version Notes (Continued)

```
Thread model: posix
InstalledDir:
  /global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm
Configuration file:
  /global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/../bin/icx.cfg
------------------------------------------------------------------------------

==============================================================================
 CC  618.tealeaf_s(peak) 621.miniswp_s(peak) 634.hpgmgfv_s(peak)
------------------------------------------------------------------------------
icc: remark #10441: The Intel(R) C++ Compiler Classic (ICC) is deprecated and
  will be removed from product release in the second half of 2023. The
  Intel(R) oneAPI DPC++/C++ Compiler (ICX) is the recommended compiler moving
  forward. Please transition to use this compiler. Use '-diag-disable=10441'
  to disable this message.
icc: command line warning #10148: option
  '-Wno-incompatible-function-pointer-types' not supported
icc (ICC) 2021.9.0 20230302
Copyright (C) 1985-2023 Intel Corporation.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
 FC  619.clvleaf_s(peak)
------------------------------------------------------------------------------
ifort (IFORT) 2021.9.0 20230302
Copyright (C) 1985-2023 Intel Corporation.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
 FC  619.clvleaf_s(base) 628.pot3d_s(base, peak) 635.weather_s(base, peak)
------------------------------------------------------------------------------
ifx (IFX) 2023.1.0 20230320
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

## Base Compiler Invocation

C benchmarks:
`mpiicc -cc=icx`

C++ benchmarks:
`mpiicpc -cxx=icpx`

Fortran benchmarks:
`mpiifort -fc=ifx`

## Base Portability Flags

605.lbm_s: `-lstdc++ -std=c++14`
613.soma_s: `-lstdc++ -std=c++14`
618.tealeaf_s: `-lstdc++ -std=c++14`
621.miniswp_s: `-lstdc++ -std=c++14`
634.hpgmgfv_s: `-lstdc++ -std=c++14`

## Base Optimization Flags

C benchmarks:
`-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512 -qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto -funroll-loops`

C++ benchmarks:
`-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512 -qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto -funroll-loops`

Fortran benchmarks:
`-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512 -qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto -funroll-loops -nostandard-realloc-lhs -align array64byte`

## Base Other Flags

C benchmarks:
`-Ispecmpitime -Wno-incompatible-function-pointer-types`

C++ benchmarks:
`-Ispecmpitime`

Fortran benchmarks:

619.clvleaf_s: `-Ispecmpitime`

## Peak Compiler Invocation

C benchmarks (except as noted below):
`mpiicc`

**(Continued on next page)**

## Peak Compiler Invocation (Continued)

605.lbm_s: `mpiicc -cc=icx`

613.soma_s: `mpiicc -cc=icx`

C++ benchmarks:
`mpiicpc -cxx=icpx`

Fortran benchmarks (except as noted below):
`mpiifort -fc=ifx`

619.clvleaf_s: `mpiifort`

## Peak Portability Flags

605.lbm_s: `-lstdc++ -std=c++14`
613.soma_s: `-lstdc++ -std=c++14`
618.tealeaf_s: `-lstdc++ -std=c++14`
621.miniswp_s: `-lstdc++ -std=c++14`
634.hpgmgfv_s: `-lstdc++ -std=c++14`

## Peak Optimization Flags

C benchmarks:

605.lbm_s: `basepeak = yes`

613.soma_s: `-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512 -qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto -funroll-loops`

618.tealeaf_s: `-O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo -qopt-zmm-usage=high -qopt-multiple-gather-scatter-by-shuffles`

621.miniswp_s: `Same as 618.tealeaf_s`

634.hpgmgfv_s: `Same as 618.tealeaf_s`

C++ benchmarks:
`-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512 -qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto -funroll-loops`

**(Continued on next page)**

## Peak Optimization Flags (Continued)

Fortran benchmarks:

619.clvleaf_s: `-O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo -qopt-zmm-usage=high -qopt-multiple-gather-scatter-by-shuffles -nostandard-realloc-lhs -align array64byte`

628.pot3d_s: `basepeak = yes`

635.weather_s: `basepeak = yes`

## Peak Other Flags

C benchmarks:
`-Ispecmpitime -Wno-incompatible-function-pointer-types`

C++ benchmarks:
`-Ispecmpitime`

Fortran benchmarks:

619.clvleaf_s: `-Ispecmpitime`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.xml`


SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2023-07-12 15:15:12-0400.
Report generated on 2023-08-16 15:02:16 by hpc2021 PS formatter v1.0.3.
Originally published on 2023-08-16.