SPEChpc™ 2021 Medium Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_med_base = 0.5616

SPEChpc 2021_med_peak = 0.5970

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
705.lbm_m	OMP	32	28	1539	0.796	1500	0.817	**1530**	**0.801**	OMP	32	28	1539	0.796	1500	0.817	**1530**	**0.801**
718.tealeaf_m	OMP	32	28	3222	0.419	3071	0.440	**3112**	**0.434**	OMP	128	7	3100	0.436	**3078**	**0.439**	3069	0.440
719.clvleaf_m	OMP	32	28	3738	0.495	3705	0.499	**3706**	**0.499**	OMP	32	28	3252	0.569	3280	0.564	**3268**	**0.566**
728.pot3d_m	OMP	32	28	**4658**	**0.397**	4656	0.397	4660	0.397	OMP	32	28	**4658**	**0.397**	4656	0.397	4660	0.397
734.hpgmgfv_m	OMP	32	28	**2070**	**0.483**	2087	0.479	2062	0.485	OMP	128	7	1968	0.508	1966	0.509	**1967**	**0.508**
735.weather_m	OMP	32	28	2555	0.939	**2544**	**0.943**	2507	0.957	OMP	128	7	2137	1.12	**2128**	**1.13**	2127	1.13

SPEChpc 2021_med_base = 0.5616

SPEChpc 2021_med_peak = 0.5970

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEChpc™ 2021 Medium Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_med_base = 0.5616

SPEChpc 2021_med_peak = 0.5970

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Hardware Summary

Type of System:	Homogenous Cluster
Compute Node:	Intel Server D50DNP2MFALACB (Xeon 8480+)
Interconnect:	Mellanox HDR
Compute Nodes Used:	8
Total Chips:	16
Total Cores:	896
Total Threads:	1792
Total Memory:	4 TB
Total Accelerators:	0
Max. Peak Threads:	28

Software Summary

Compiler:	Intel oneAPI Compiler 2023.1.0
MPI Library:	Intel MPI Library 2021.9 for Linux OS
Other MPI Info:	None
Other Software:	None
Base Parallel Model:	OMP
Base Ranks Run:	32
Base Threads Run:	28
Peak Parallel Models:	OMP
Minimum Peak Ranks:	32
Maximum Peak Ranks:	128
Max. Peak Threads:	28
Min. Peak Threads:	7

Node Description: Intel Server D50DNP2MFALACB (Xeon 8480+)

Hardware

Number of nodes:	8
Uses of the node:	Compute
Vendor:	Intel
Model:	Intel Server D50DNP2MFALACB (Xeon 8480+)
CPU Name:	Intel Xeon Platinum 8480+
CPU(s) orderable:	1, 2 chips
Chips enabled:	2
Cores enabled:	112
Cores per chip:	56
Threads per core:	2
CPU Characteristics:	Turbo Boost Technology up to 3.8 GHz
CPU MHz:	2000
Primary Cache:	32 KB I + 48 KB D on chip per core
Secondary Cache:	2 MB I+D on chip per core
L3 Cache:	105 MB I+D on chip per chip
Other Cache:	None
Memory:	512 GB (16 x 32 GB 2Rx8 PC5-4800B)
Disk Subsystem:	1 x 1 TB NVMe U.2 2.5" SSD
Other Hardware:	None
Accel Count:	None
Accel Model:	None
Accel Vendor:	None
Accel Type:	None
Accel Connection:	None
Accel ECC enabled:	None
Accel Description:	None
Adapter:	Mellanox ConnectX-6 HDR
Number of Adapters:	1
Slot Type:	PCI-Express 4.0 x16
Data Rate:	200Gbit/s
Ports Used:	1
Interconnect Type:	Mellanox HDR

Software

Accelerator Driver:	None
Adapter:	Mellanox ConnectX-6 HDR
Adapter Driver:	5.9-0.5.5
Adapter Firmware:	20.36.1010
Operating System:	Rocky Linux 8.7 (Green Obsidian) 4.18.0-372.32.1.el8_6.crt3.x86_64
Local File System:	NFS
Shared File System:	PANASAS FS
System State:	Multi-user
Other Software:	None

Interconnect Description: Mellanox HDR

Hardware

Vendor:	Mellanox
Model:	Mellanox HDR
Switch Model:	Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch
Number of Switches:	18
Number of Ports:	40
Data Rate:	200 Gbit/s
Firmware:	20.36.1010
Topology:	Fat-tree
Primary Use:	MPI Traffic

Software

: --

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
The PANASAS filesystem as described on this result page was formerly
generally available.  At the time of this publication, it may
not be shipping, and/or may not be supported, and/or may fail
to meet other tests of General Availability described in the
SPEC HPG Policy document, http://www.spec.org/hpg/policy.html
```

Compiler Version Notes

```
==============================================================================
 CC  705.lbm_m(base, peak) 718.tealeaf_m(base, peak) 734.hpgmgfv_m(base,
     peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
  /global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm
Configuration file:
  /global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/../bin/icx.cfg
------------------------------------------------------------------------------

==============================================================================
 FC  719.clvleaf_m(peak)
------------------------------------------------------------------------------
ifort (IFORT) 2021.9.0 20230302
Copyright (C) 1985-2023 Intel Corporation.  All rights reserved.
```

(Continued on next page)

Compiler Version Notes (Continued)

```
------------------------------------------------------------------------------

==============================================================================
 FC  719.clvleaf_m(base) 728.pot3d_m(base, peak) 735.weather_m(base, peak)
------------------------------------------------------------------------------
ifx (IFX) 2023.1.0 20230320
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
`mpiicc -cc=icx`

Fortran benchmarks:
`mpiifort -fc=ifx`

Base Portability Flags

705.lbm_m: `-lstdc++ -std=c++14`
718.tealeaf_m: `-lstdc++ -std=c++14`
734.hpgmgfv_m: `-lstdc++ -std=c++14`

Base Optimization Flags

C benchmarks:
`-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512 -qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto -funroll-loops`

Fortran benchmarks:
`-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512 -qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto -funroll-loops -nostandard-realloc-lhs -align array64byte`

Base Other Flags

C benchmarks (except as noted below):
`-Ispecmpitime -Wno-incompatible-function-pointer-types`

(Continued on next page)

Base Other Flags (Continued)

734.hpgmgfv_m: `-Ispecmpitime -Wno-incompatible-function-pointer-types`

Fortran benchmarks:

719.clvleaf_m: `-Ispecmpitime`

Peak Compiler Invocation

C benchmarks:
`mpiicc -cc=icx`

Fortran benchmarks (except as noted below):
`mpiifort -fc=ifx`

719.clvleaf_m: `mpiifort`

Peak Portability Flags

705.lbm_m: `-lstdc++ -std=c++14`
718.tealeaf_m: `-lstdc++ -std=c++14`
734.hpgmgfv_m: `-lstdc++ -std=c++14`

Peak Optimization Flags

C benchmarks:

705.lbm_m: `basepeak = yes`

718.tealeaf_m: `-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512 -qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto -funroll-loops`

734.hpgmgfv_m: `Same as 718.tealeaf_m`

Fortran benchmarks:

719.clvleaf_m: `-O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo -qopt-zmm-usage=high`

(Continued on next page)

Peak Optimization Flags (Continued)

719.clvleaf_m (continued):
-qopt-multiple-gather-scatter-by-shuffles
-nostandard-realloc-lhs -align array64byte

728.pot3d_m: basepeak = yes

735.weather_m: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp
-ffast-math -flto -funroll-loops
-qopt-streaming-stores=always -nostandard-realloc-lhs
-align array64byte

Peak Other Flags

C benchmarks (except as noted below):
-Ispecmpitime -Wno-incompatible-function-pointer-types

734.hpgmgfv_m: -Ispecmpitime -Wno-incompatible-function-pointer-types

Fortran benchmarks:

719.clvleaf_m: -Ispecmpitime

The flags file that was used to format this result can be browsed at
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2023-07-13 15:30:16-0400.
Report generated on 2025-06-06 13:08:51 by hpc2021 PS formatter v112.
Originally published on 2023-09-06.