



SPEChpc™ 2021 Large Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_lrg_base = 1.23

SPEChpc 2021_lrg_peak = 1.25

hpc2021 License: 13


Test Sponsor: Intel

Tested by: Intel

Test Date: Jul-2023

Hardware Availability: Jan-2023

Software Availability: Apr-2023



Results Table

Benchmark	Base								Peak							
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio
805.lbm_l	OMP	3584	1	1450	1.88	1456	1.87	1450	1.88	OMP	3584	1	1450	1.88	1456	1.87
818.tealeaf_l	OMP	3584	1	1514	0.958	1517	0.956	1528	0.949	OMP	3584	1	1514	0.958	1517	0.956
819.clvleaf_l	OMP	3584	1	2935	0.716	2792	0.752	2876	0.730	OMP	3584	1	2509	0.837	2722	0.771
828.pot3d_l	OMP	3584	1	4847	0.939	4879	0.932	4849	0.938	OMP	1792	2	4816	0.945	4813	0.945
834.hpgmgfv_l	OMP	3584	1	2030	1.65	2003	1.67	2004	1.67	OMP	3584	1	2030	1.65	2003	1.67
835.weather_l	OMP	3584	1	2045	1.67	1980	1.73	2105	1.63	OMP	3584	1	2045	1.67	1980	1.73

SPEChpc 2021_lrg_base = 1.23

SPEChpc 2021_lrg_peak = 1.25

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Large Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_lrg_base = 1.23

SPEChpc 2021_lrg_peak = 1.25

hpc2021 License: 13

Test Sponsor: Intel

Tested by: Intel

Test Date: Jul-2023

Hardware Availability: Jan-2023

Software Availability: Apr-2023

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: Intel Server D50DNP2MFALACB (Xeon 8480+)
Interconnect: Mellanox HDR
Compute Nodes Used: 32
Total Chips: 64
Total Cores: 3584
Total Threads: 7168
Total Memory: 16 TB
Total Accelerators: 0
Max. Peak Threads: 2

Software Summary

Compiler: Intel oneAPI Compiler 2023.1.0
MPI Library: Intel MPI Library 2021.9 for Linux OS
Other MPI Info: None
Other Software: None
Base Parallel Model: OMP
Base Ranks Run: 3584
Base Threads Run: 1
Peak Parallel Models: OMP
Minimum Peak Ranks: 1792
Maximum Peak Ranks: 3584
Max. Peak Threads: 2
Min. Peak Threads: 1

Node Description: Intel Server D50DNP2MFALACB (Xeon 8480+)

Hardware

Number of nodes: 32
Uses of the node: Compute
Vendor: Intel
Model: Intel Server D50DNP2MFALACB (Xeon 8480+)
CPU Name: Intel Xeon Platinum 8480+
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 112
Cores per chip: 56
Threads per core: 2
CPU Characteristics: Turbo Boost Technology up to 3.8 GHz
CPU MHz: 2000
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 105 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (16 x 32 GB 2Rx8 PC5-4800B)
Disk Subsystem: 1 x 1 TB NVMe U.2 2.5" SSD
Other Hardware: None
Accel Count: None
Accel Model: None
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: Mellanox ConnectX-6 HDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 200Gbit/s
Ports Used: 1
Interconnect Type: Mellanox HDR

Software

Accelerator Driver: None
Adapter: Mellanox ConnectX-6 HDR
Adapter Driver: 5.9-0.5.5
Adapter Firmware: 20.36.1010
Operating System: Rocky Linux 8.7 (Green Obsidian)
4.18.0-372.32.1.el8_6.crt3.x86_64
Local File System: NFS
Shared File System: PANASAS FS
System State: Multi-user
Other Software: None



SPEChpc™ 2021 Large Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_lrg_base = 1.23

SPEChpc 2021_lrg_peak = 1.25

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Interconnect Description: Mellanox HDR

Hardware

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch
Number of Switches: 18
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 20.36.1010
Topology: Fat-tree
Primary Use: MPI Traffic

Software

: --

Submit Notes

The config file option 'submit' was used.

General Notes

The PANASAS filesystem as described on this result page was formerly generally available. At the time of this publication, it may not be shipping, and/or may not be supported, and/or may fail to meet other tests of General Availability described in the SPEC HPG Policy document, <http://www.spec.org/hpg/policy.html>

Compiler Version Notes

=====
CC 805.lbm_l(base, peak) 818.tealeaf_l(base, peak) 834.hpgmgfv_l(base, peak)
=====

Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm
Configuration file:
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/./bin/icx.cfg

=====
FC 819.clvleaf_l(peak) 828.pot3d_l(peak)
=====

ifort (IFORT) 2021.9.0 20230302
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

(Continued on next page)



SPEChpc™ 2021 Large Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_lrg_base = 1.23

SPEChpc 2021_lrg_peak = 1.25

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Compiler Version Notes (Continued)

=====

FC 819.clvleaf_l(base) 828.pot3d_l(base) 835.weather_l(base, peak)

ifx (IFX) 2023.1.0 20230320
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:
mpiicc -cc=icx

Fortran benchmarks:
mpiifort -fc=ifx

Base Portability Flags

805.lbm_l: -lstdc++ -std=c++14
818.tealeaf_l: -lstdc++ -std=c++14
834.hpgmgfv_l: -lstdc++ -std=c++14

Base Optimization Flags

C benchmarks:
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops

Fortran benchmarks:
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops -nostandard-realloc-lhs -align array64byte

Base Other Flags

C benchmarks (except as noted below):
-Ispecmpitime -Wno-incompatible-function-pointer-types

(Continued on next page)



SPEChpc™ 2021 Large Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_lrg_base = 1.23

SPEChpc 2021_lrg_peak = 1.25

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Base Other Flags (Continued)

834.hpgmgfv_l: -Ispecmpitime -Wno-incompatible-function-pointer-types

Fortran benchmarks:

819.clvleaf_l: -Ispecmpitime

Peak Compiler Invocation

C benchmarks:
mpiicc -cc=icx

Fortran benchmarks (except as noted below):
mpiifort

835.weather_l: mpiifort -fc=ifx

Peak Portability Flags

805.lbm_l: -lstdc++ -std=c++14
818.tealeaf_l: -lstdc++ -std=c++14
834.hpgmgfv_l: -lstdc++ -std=c++14

Peak Optimization Flags

C benchmarks:

805.lbm_l: basepeak = yes

818.tealeaf_l: basepeak = yes

834.hpgmgfv_l: basepeak = yes

Fortran benchmarks:

819.clvleaf_l: -O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo
-qopt-zmm-usage=high
-qopt-multiple-gather-scatter-by-shuffles
-nostandard-realloc-lhs -align array64byte

(Continued on next page)



SPEChpc™ 2021 Large Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_lrg_base = 1.23

SPEChpc 2021_lrg_peak = 1.25

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Peak Optimization Flags (Continued)

828.pot3d_l: Same as 819.clvleaf_l

835.weather_l: basepeak = yes

Peak Other Flags

C benchmarks (except as noted below):

-Ispecmpitime -Wno-incompatible-function-pointer-types

834.hpgmgfv_l: -Ispecmpitime -Wno-incompatible-function-pointer-types

Fortran benchmarks:

819.clvleaf_l: -Ispecmpitime

The flags file that was used to format this result can be browsed at

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2023-07-20 07:02:55-0400.

Report generated on 2025-06-06 13:08:58 by hpc2021 PDF formatter v112.

Originally published on 2023-09-06.