



SPEC® OMPG2012 Result

Copyright 2012-2014 Standard Performance Evaluation Corporation

Intel

SPECompG_peak2012 = 18.7

S4TR1SY4Q (Intel Xeon E7-4890 v2)

SPECompG_base2012 = 17.4

OMP2012 license:13


Test date: Feb-2014

Test sponsor: Intel

Hardware Availability: Feb-2014

Tested by: Intel

Software Availability: Jun-2013



Hardware

CPU Name:	Intel Xeon E7-4890 v2
CPU Characteristics:	
CPU MHz:	2800
CPU MHz Maximum:	3400
FPU:	Integrated
CPU(s) enabled:	60 cores, 4 chips, 15 cores/chip, 2 threads/core
CPU(s) orderable:	1,2,3,4 Chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	38400 KB I+D on chip per chip
Other Cache:	None
Memory:	512 GB (32 x 16 GB 2Rx4 PC3-12800R-11, ECC)
Disk Subsystem:	Panasas ActiveStor 14
Other Hardware:	--
Base Threads Run:	120
Minimum Peak Threads:	60

Software

Operating System:	Red Hat Enterprise Linux Server release 6.4
Compiler:	C/C++/Fortran: Version 13.1.3 of Intel Composer XE for Linux Build 20130607
Auto Parallel:	No
File System:	Linux ext3
System State:	Default
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other Software:	None

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2014 Standard Performance Evaluation Corporation

Intel

SPECompG_peak2012 = 18.7

S4TR1SY4Q (Intel Xeon E7-4890 v2)

SPECompG_base2012 = 17.4

OMP2012 license:13

Test date: Feb-2014

Test sponsor: Intel

Hardware Availability: Feb-2014

Tested by: Intel

Software Availability: Jun-2013

Maximum Peak Threads: 120

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	120	231	20.1	<u>230</u>	<u>20.1</u>	226	20.5	120	<u>188</u>	<u>24.6</u>	189	24.5	188	24.7
351.bwaves	120	<u>218</u>	<u>20.8</u>	218	20.8	218	20.8	60	193	23.5	<u>193</u>	<u>23.5</u>	192	23.6
352.nab	120	<u>285</u>	<u>13.7</u>	285	13.7	285	13.6	120	270	14.4	<u>269</u>	<u>14.5</u>	269	14.5
357.bt331	120	229	20.7	229	20.7	<u>229</u>	<u>20.7</u>	120	224	21.2	225	21.1	<u>224</u>	<u>21.1</u>
358.botsalgn	120	<u>328</u>	<u>13.3</u>	328	13.3	328	13.3	120	328	13.3	327	13.3	<u>328</u>	<u>13.3</u>
359.botsspar	120	528	9.95	530	9.91	<u>528</u>	<u>9.94</u>	60	425	12.3	425	12.3	<u>425</u>	<u>12.3</u>
360.ilbdc	120	290	12.3	<u>290</u>	<u>12.3</u>	290	12.3	120	290	12.3	<u>290</u>	<u>12.3</u>	290	12.3
362.fma3d	120	<u>338</u>	<u>11.2</u>	338	11.2	368	10.3	120	367	10.4	<u>337</u>	<u>11.3</u>	337	11.3
363.swim	120	<u>263</u>	<u>17.2</u>	263	17.2	263	17.2	60	<u>232</u>	<u>19.6</u>	231	19.6	233	19.4
367.imagick	120	329	21.4	<u>329</u>	<u>21.4</u>	330	21.3	120	330	21.3	<u>329</u>	<u>21.4</u>	328	21.4
370.mgrid331	120	282	15.7	282	15.7	<u>282</u>	<u>15.7</u>	60	277	16.0	277	15.9	<u>277</u>	<u>16.0</u>
371.applu331	120	164	37.0	163	37.1	<u>164</u>	<u>37.0</u>	120	<u>164</u>	<u>37.0</u>	164	37.0	163	37.1
372.smithwa	120	<u>183</u>	<u>29.2</u>	183	29.2	181	29.6	60	<u>143</u>	<u>37.4</u>	144	37.3	143	37.5
376.kdtree	120	258	17.4	259	17.4	<u>258</u>	<u>17.4</u>	120	258	17.4	<u>259</u>	<u>17.4</u>	259	17.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /panfs/projects/innl/aknyaze1/OMP2012/1.0/Docs/sysinfo
$Rev: 395 $ $Date:: 2012-07-25 #$ 8f8c0fe9e19c658963a1e67685e50647
running on eix05 Mon Feb 3 14:08:28 2014
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E7-4890 v2 @ 2.80GHz
        4 "physical id"s (chips)
        120 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 15
siblings : 30
physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 2: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
physical 3: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
cache size : 38400 KB
```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2014 Standard Performance Evaluation Corporation

Intel

SPECompG_peak2012 = 18.7

S4TR1SY4Q (Intel Xeon E7-4890 v2)

SPECompG_base2012 = 17.4

OMP2012 license:13

Test date: Feb-2014

Test sponsor: Intel

Hardware Availability: Feb-2014

Tested by: Intel

Software Availability: Jun-2013

Platform Notes (Continued)

```
From /proc/meminfo
  MemTotal:      529160992 kB
  HugePages_Total:       0
  Hugepagesize:     2048 kB
```

```
/usr/bin/lsb_release -d
  Red Hat Enterprise Linux Server release 6.4 (Santiago)
```

```
From /etc/*release* /etc/*version*
  redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
  system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
  system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
  Linux eix05 2.6.32-358.6.2.el6.x86_64.crt1 #4 SMP Fri May 17 15:33:33 MDT
  2013 x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Jan 27 20:46
```

```
SPEC is set to: /panfs/projects/innl/aknyazel/OMP2012/1.0
  Filesystem      Type  Size  Used Avail Use% Mounted on
  panfs://36.101.211.1/projects
            panfs    28T   18T   9.7T  65% /panfs/projects
```

```
Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'
```

```
(End of data from sysinfo program)
```

General Notes

```
=====
BIOS settings: Default
  Intel Turbo Boost Technology (Turbo) : Enabled
  Transparent Huge Pages Disabled via "echo never > /sys/kernel/mm/redhat_transparent_hugepage/enabled"
```

```
=====
General OMP Library Settings
  ENV_KMP_LIBRARY=throughput
  ENV_KMP_STACKSIZE=190M
  ENV_KMP_BLOCKTIME=infinite
  ENV_OMP_DYNAMIC=FALSE
  ENV_OMP_NESTED=FALSE
  ENV_OMP_SCHEDULE=static
```

```
=====
General base OMP Library Settings
  ENV_KMP_AFFINITY=compact,0,granularity=fine
```

```
=====
General peak OMP Library Settings
  ENV_KMP_AFFINITY=compact,0,granularity=fine
  Continued on next page
```



SPEC OMPG2012 Result

Copyright 2012-2014 Standard Performance Evaluation Corporation

Intel

SPECompG_peak2012 = 18.7

S4TR1SY4Q (Intel Xeon E7-4890 v2)

SPECompG_base2012 = 17.4

OMP2012 license:13

Test date: Feb-2014

Test sponsor: Intel

Hardware Availability: Feb-2014

Tested by: Intel

Software Availability: Jun-2013

General Notes (Continued)

=====
Per benchmark peak OMP Library Settings

=====
351.bwaves:peak:
 ENV_KMP_AFFINITY=compact,1,granularity=fine
 ENV_OMP_SCHEDULE=static,1

=====
357.bt331:peak:
 ENV_OMP_SCHEDULE=static,1

=====
359.botsspar:peak:
 ENV_KMP_AFFINITY=compact,1,granularity=fine
 ENV_OMP_SCHEDULE=guided

=====
362.fma3d:peak:
 ENV_OMP_SCHEDULE=static,1

=====
363.swim:peak:
 ENV_KMP_AFFINITY=compact,1,granularity=fine

=====
370.mgrid331:peak:
 ENV_KMP_AFFINITY=compact,1,granularity=fine

=====
372.smithwa:peak:
 ENV_OMP_SCHEDULE=static,1
 ENV_KMP_AFFINITY=compact,1,granularity=fine

Base Compiler Invocation

C benchmarks:
 icc

C++ benchmarks:
 icpc

Fortran benchmarks:
 ifort



SPEC OMPG2012 Result

Copyright 2012-2014 Standard Performance Evaluation Corporation

Intel

SPECompG_peak2012 = 18.7

S4TR1SY4Q (Intel Xeon E7-4890 v2)

SPECompG_base2012 = 17.4

OMP2012 license:13

Test date: Feb-2014

Test sponsor: Intel

Hardware Availability: Feb-2014

Tested by: Intel

Software Availability: Jun-2013

Base Portability Flags

350.md: -FR
357.bt331: -mcmodel=medium
363.swim: -mcmodel=medium
367.imagick: -std=c99

Base Optimization Flags

C benchmarks:

-O2 -openmp -ipo -xAVX -ansi-alias

C++ benchmarks:

-O2 -openmp -ipo -xAVX -ansi-alias

Fortran benchmarks:

-O2 -openmp -ipo -xAVX -align array64byte

Peak Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Peak Portability Flags

350.md: -FR
357.bt331: -mcmodel=medium
363.swim: -mcmodel=medium
367.imagick: -std=c99

Peak Optimization Flags

C benchmarks:

352.nab: -O3 -openmp -ipo -xAVX -fno-alias -opt-malloc-options=1
-opt-calloc -fp-model fast=2 -no-prec-div -no-prec-sqrt
-ansi-alias

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2014 Standard Performance Evaluation Corporation

Intel

SPECompG_peak2012 = 18.7

S4TR1SY4Q (Intel Xeon E7-4890 v2)

SPECompG_base2012 = 17.4

OMP2012 license:13

Test date: Feb-2014

Test sponsor: Intel

Hardware Availability: Feb-2014

Tested by: Intel

Software Availability: Jun-2013

Peak Optimization Flags (Continued)

358.botsalgn: -O2 -openmp -ipo -xAVX -fno-alias

359.botsspar: -O3 -openmp -ipo -xAVX -fno-alias -ansi-alias

367.imagick: Same as 358.botsalgn

372.smithwa: -O2 -openmp -ipo -xSSE4.2 -fno-alias
-opt-streaming-stores always -opt-malloc-options=1
-ansi-alias

C++ benchmarks:

-O3 -openmp -ipo -xAVX -fno-alias -ansi-alias

Fortran benchmarks:

350.md: -O2 -openmp -ipo -xAVX -fno-alias -opt-malloc-options=1
-fp-model fast=2 -no-prec-div -no-prec-sqrt
-align array64byte

351.bwaves: -O3 -openmp -ipo -xAVX -fno-alias -fp-model fast=2
-no-prec-div -no-prec-sqrt -align array64byte

357.bt331: Same as 351.bwaves

360.ilbdc: -O3 -openmp -ipo -xAVX -opt-malloc-options=1
-align array64byte

362.fma3d: -O3 -openmp -ipo -xAVX -fno-alias -align array64byte

363.swim: -O3 -openmp -ipo -xSSE4.2 -fno-alias
-opt-streaming-stores always -opt-malloc-options=3
-align array64byte

370.mgrid331: -O2 -openmp -ipo -xSSE4.2 -fno-alias
-opt-malloc-options=3 -align array64byte

371.applu331: -O2 -openmp -ipo -xAVX -align array64byte

The flags file that was used to format this result can be browsed at

<http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20140219.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20140219.xml>



SPEC OMPG2012 Result

Copyright 2012-2014 Standard Performance Evaluation Corporation

Intel

SPECompG_peak2012 = 18.7

S4TR1SY4Q (Intel Xeon E7-4890 v2)

SPECompG_base2012 = 17.4

OMP2012 license:13

Test date: Feb-2014

Test sponsor: Intel

Hardware Availability: Feb-2014

Tested by: Intel

Software Availability: Jun-2013

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.0.

Report generated on Tue Jul 22 13:38:04 2014 by SPEC OMP2012 PS/PDF formatter v541.

Originally published on 19 February 2014.