



SPEC® OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Huawei

SPECompG_peak2012 = 13.8

Huawei RH2288H V3 (Intel Xeon E5-2699 v4)

SPECompG_base2012 = 12.4

OMP2012 license:27


Test sponsor: Huawei

Tested by: Huawei

Test date: Nov-2016

Hardware Availability: Apr-2016

Software Availability: Aug-2016



Hardware

CPU Name: Intel Xeon E5-2699 v4
CPU Characteristics: Intel Turbo Boost Technology up to 3.60 GHz
CPU MHz: 2200
CPU MHz Maximum: 3600
FPU: Integrated
CPU(s) enabled: 44 cores, 2 chips, 22 cores/chip, 2 threads/core
CPU(s) orderable: 1,2 Chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per cores
L3 Cache: 55 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (16 x 32 GB 2Rx4 PC4-2400T-R)
Disk Subsystem: 1 X 1 TB SATA, 7200 RPM
Other Hardware: None
Base Threads Run: 88
Minimum Peak Threads: 44

Software

Operating System: Red Hat Enterprise Linux Server release 7.2
Compiler: Kernel 3.10.0-327.el7.x86_64
C/C++/Fortran: Version 16.0.3.210 of Intel Composer XE
for Linux Build 20160415
Auto Parallel: No
File System: Linux ext4
System State: Default
Base Pointers: 64-bit
Peak Pointers: 64-bit
Other Software: None

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Huawei

SPECompG_peak2012 = 13.8

Huawei RH2288H V3 (Intel Xeon E5-2699 v4)

SPECompG_base2012 = 12.4

OMP2012 license:27

Test date: Nov-2016

Test sponsor: Huawei

Hardware Availability: Apr-2016

Tested by: Huawei

Software Availability: Aug-2016

Maximum Peak Threads: 88

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	88	256	18.1	259	17.9	265	17.5	88	214	21.7	214	21.6	214	21.7
351.bwaves	88	358	12.6	357	12.7	358	12.6	44	349	13.0	350	12.9	349	13.0
352.nab	88	290	13.4	280	13.9	280	13.9	88	261	14.9	261	14.9	262	14.9
357.bt331	88	285	16.6	287	16.5	286	16.6	88	271	17.5	271	17.5	271	17.5
358.botsalgn	88	370	11.7	370	11.8	370	11.8	88	362	12.0	362	12.0	362	12.0
359.botsspar	88	567	9.26	570	9.22	569	9.22	44	516	10.2	516	10.2	516	10.2
360.ilbdc	88	393	9.06	393	9.05	394	9.03	88	393	9.06	393	9.05	394	9.03
362.fma3d	88	377	10.1	380	10.0	388	9.78	88	377	10.1	380	10.0	388	9.78
363.swim	88	471	9.61	471	9.63	471	9.61	88	471	9.61	471	9.63	471	9.61
367.imagick	88	511	13.7	511	13.7	511	13.7	88	511	13.7	512	13.7	512	13.7
370.mgrid331	88	525	8.42	527	8.39	526	8.40	44	507	8.72	507	8.71	508	8.71
371.applu331	88	283	21.4	299	20.3	289	21.0	88	284	21.3	290	20.9	285	21.3
372.smithwa	88	408	13.1	400	13.4	403	13.3	44	143	37.4	144	37.3	143	37.4
376.kdtree	88	369	12.2	370	12.2	369	12.2	88	366	12.3	365	12.3	365	12.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /omp2012/Docs/sysinfo
$Rev: 395 $ $Date:: 2012-07-25 #$
running on localhost.localdomain Fri Nov 11 15:42:21 2016
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E5-2699 v4 @ 2.20GHz
        2 "physical id"s (chips)
        88 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
        cpu cores : 22
        siblings : 44
physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 16 17 18 19 20 21 24 25 26 27
        28
physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 16 17 18 19 20 21 24 25 26 27
        28
cache size : 28160 KB
```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Huawei

Huawei RH2288H V3 (Intel Xeon E5-2699 v4)

SPECompG_peak2012 = 13.8

SPECompG_base2012 = 12.4

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Nov-2016

Hardware Availability: Apr-2016

Software Availability: Aug-2016

Platform Notes (Continued)

From /proc/meminfo

```
MemTotal:      527785168 kB
HugePages_Total:      0
Hugepagesize:     2048 kB
```

From /etc/*release* /etc/*version*

```
os-release:
  NAME="Red Hat Enterprise Linux Server"
  VERSION="7.2 (Maipo)"
  ID="rhel"
  ID_LIKE="fedora"
  VERSION_ID="7.2"
  PRETTY_NAME="Red Hat Enterprise Linux Server 7.2 (Maipo)"
  ANSI_COLOR="0;31"
  CPE_NAME="cpe:/o:redhat:enterprise_linux:7.2:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.2 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.2 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.2:ga:server
```

uname -a:

```
Linux localhost.localdomain 3.10.0-327.el7.x86_64 #1 SMP Thu Oct 29 17:29:29
EDT 2015 x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Nov 10 17:33

SPEC is set to: /omp2012

```
Filesystem      Type  Size  Used  Avail Use% Mounted on
/dev/sda2      xfs   254G   82G  172G  33%  /
```

Additional information from dmidecode:

```
BIOS Insyde Corp. 3.32 09/14/2016
Memory:
  16x Micron 36ASF4G72PZ-2G3A1 32 GB 2400 MHz 2 rank
  8x NO DIMM NO DIMM
```

(End of data from sysinfo program)

General Notes

=====

```
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
BIOS settings notes:
Power Policy set to Performance
Set Patrol Scrub to Disable
QPI Snoop Mode set to Cluster on Die
General OMP Library Settings
ENV_KMP_LIBRARY=turnaround
ENV_OMP_SCHEDULE=static
ENV_KMP_STACKSIZE=256M
ENV_OMP_DYNAMIC=FALSE
```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Huawei

Huawei RH2288H V3 (Intel Xeon E5-2699 v4)

SPECompG_peak2012 = 13.8

SPECompG_base2012 = 12.4

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Nov-2016

Hardware Availability: Apr-2016

Software Availability: Aug-2016

General Notes (Continued)

```
ENV_OMP_NESTED=FALSE
ENV_KMP_AFFINITY=compact,0
=====
Per benchmark peak OMP Library Settings

=====
351.bwaves:peak:
    ENV_KMP_AFFINITY=compact,1
    ENV_OMP_SCHEDULE=static,1
=====
357.bt331:peak
    ENV_OMP_SCHEDULE=static,1
=====
359.botsspar:peak:
    ENV_KMP_AFFINITY=compact,1
    ENV_OMP_SCHEDULE=guided

=====
370.mgrid331:peak
    ENV_KMP_AFFINITY=compact,1
=====
372.smithwa:peak:
    ENV_KMP_AFFINITY=compact,1
    ENV_OMP_SCHEDULE=static,1
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Base Portability Flags

```
350.md: -FR
357.bt331: -mcmodel=medium
363.swim: -mcmodel=medium
367.imagick: -std=c99
```



SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Huawei

Huawei RH2288H V3 (Intel Xeon E5-2699 v4)

SPECompG_peak2012 = 13.8

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Nov-2016

Hardware Availability: Apr-2016

Software Availability: Aug-2016

Base Optimization Flags

C benchmarks:

-O2 -openmp -ipo -xCORE-AVX2 -ansi-alias

C++ benchmarks:

-O2 -openmp -ipo -xCORE-AVX2 -ansi-alias

Fortran benchmarks:

-O2 -openmp -ipo -xCORE-AVX2 -align array64byte

Peak Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Peak Portability Flags

350.md: -FR

357.bt331: -mcmodel=medium

363.swim: -mcmodel=medium

367.imagick: -std=c99

Peak Optimization Flags

C benchmarks:

352.nab: -O3 -openmp -ipo -xCORE-AVX2 -fno-alias
-opt-malloc-options=1 -opt-calloc -fp-model fast=2
-no-prec-div -no-prec-sqrt -ansi-alias

358.botsalgn: -O3 -openmp -ipo -xCORE-AVX2 -fno-alias -ansi-alias

359.botsspar: Same as 358.botsalgn

367.imagick: -O2 -openmp -ipo -xCORE-AVX2 -ansi-alias

372.smithwa: -O2 -openmp -ipo -xCORE-AVX2 -fno-alias
-opt-streaming-stores always -opt-malloc-options=1
-ansi-alias

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Huawei

Huawei RH2288H V3 (Intel Xeon E5-2699 v4)

SPECompG_peak2012 = 13.8

SPECompG_base2012 = 12.4

OMP2012 license:27

Test sponsor: Huawei

Tested by: Huawei

Test date: Nov-2016

Hardware Availability: Apr-2016

Software Availability: Aug-2016

Peak Optimization Flags (Continued)

C++ benchmarks:

```
-O3 -openmp -ipo -xCORE-AVX2 -fno-alias -ansi-alias
```

Fortran benchmarks:

```
350.md: -O2 -openmp -ipo -xCORE-AVX2 -fno-alias  
-opt-malloc-options=1 -fp-model fast=2 -no-prec-div  
-no-prec-sqrt -align array64byte
```

```
351.bwaves: -O3 -openmp -ipo -xCORE-AVX2 -fno-alias -fp-model fast=2  
-no-prec-div -no-prec-sqrt -align array64byte
```

357.bt331: Same as 351.bwaves

360.ilbdc: basepeak = yes

362.fma3d: basepeak = yes

363.swim: basepeak = yes

```
370.mgrid331: -O2 -openmp -ipo -xCORE-AVX2 -fno-alias  
-opt-malloc-options=3 -align array64byte
```

```
371.applu331: -O2 -openmp -ipo -xCORE-AVX2 -align array64byte
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20161208.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/omp2012/flags/Intel-ic13.0-linux64.20161208.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.0.

Report generated on Thu Dec 8 11:07:50 2016 by SPEC OMP2012 PS/PDF formatter v541.

Originally published on 7 December 2016.