



SPEC® OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Colfax International

(Test Sponsor: Indiana University)

Intel Xeon Phi 7210, 1.30GHz,
SMT off, Turbo off, flat (MCDRAM Preferred)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.19

OMP2012 license:3440A


Test date: Aug-2016

Test sponsor: Indiana University

Hardware Availability: Aug-2016

Tested by: Indiana University

Software Availability: Apr-2016



Hardware

CPU Name: Intel Xeon Phi 7210
CPU Characteristics: Intel Turbo Boost Technology off, Simultaneous Multithreading (SMT) off
CPU MHz: 1300
CPU MHz Maximum: 1500
FPU: Integrated
CPU(s) enabled: 64 cores, 1 chip, 64 cores/chip, 4 threads/core
CPU(s) orderable: 1 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per two cores
L3 Cache: None
Other Cache: None
Memory: 96 GB (6 x 16 GB 2Rx8 PC4-2400T-REB-11, ECC)
Disk Subsystem: Intel S3510 SSD 800GB, SATA3
Other Hardware: None
Base Threads Run: 64

Software

Operating System: CentOS Linux release 7.2.1511
Compiler: 3.10.0-327.13.1.el7.xppsl_1.3.3.151.x86_64
C/C++/Fortran: Version 16.0.3.210 of Intel Composer XE 2016 for Linux Build 20160415
Auto Parallel: No
File System: ext4
System State: Runlevel 3 (multi-user with networking)
Base Pointers: 64-bit
Peak Pointers: Not Applicable
Other Software: None

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Colfax International

(Test Sponsor: Indiana University)

Intel Xeon Phi 7210, 1.30GHz,
SMT off, Turbo off, flat (MCDRAM Preferred)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.19

OMP2012 license:3440A

Test date: Aug-2016

Test sponsor: Indiana University

Hardware Availability: Aug-2016

Tested by: Indiana University

Software Availability: Apr-2016

Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

Benchmark	Base								Peak							
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	64	1071	4.32	1069	4.33	1067	4.34									
351.bwaves	64	318	14.2	319	14.2	320	14.1									
352.nab	64	780	4.99	781	4.98	780	4.99									
357.bt331	64	603	7.86	601	7.89	604	7.85									
358.botsalgn	64	1360	3.20	1359	3.20	1359	3.20									
359.botsspar	64	3338	1.57	3347	1.57	3342	1.57									
360.ilbdc	64	286	12.5	285	12.5	286	12.5									
362.fma3d	64	719	5.28	719	5.28	719	5.28									
363.swim	64	180	25.1	180	25.2	179	25.2									
367.imagick	64	982	7.16	985	7.14	984	7.14									
370.mgrid331	64	242	18.3	236	18.7	237	18.7									
371.applu331	64	441	13.8	439	13.8	443	13.7									
372.smithwa	64	584	9.18	584	9.18	585	9.16									
376.kdtree	64	1544	2.92	1545	2.91	1546	2.91									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
submit = numactl -p 1 \$command

Platform Notes

Sysinfo program /home/lijunj/SPEC/omp2012-1.1-run/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on kn11.uits.indiana.edu Thu Oct 13 16:12:58 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon Phi(TM) CPU 7210 @ 1.30GHz
        1 "physical id"s (chips)
        64 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 64
```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Colfax International

(Test Sponsor: Indiana University)

Intel Xeon Phi 7210, 1.30GHz,
SMT off, Turbo off, flat (MCDRAM Preferred)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.19

OMP2012 license:3440A

Test date: Aug-2016

Test sponsor: Indiana University

Hardware Availability: Aug-2016

Tested by: Indiana University

Software Availability: Apr-2016

Platform Notes (Continued)

```
siblings : 64
physical 0: cores 0 1 2 3 6 7 10 11 12 13 14 15 18 19 20 21 22 23 24 25 26
27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51
52 53 56 57 58 59 60 61 62 63 64 65 68 69 70 71 72 73
cache size : 1024 kB

From /proc/meminfo
MemTotal:           115216920 kB
HugePages_Total:    0
Hugepagesize:       2048 kB

/usr/bin/lsb_release -d
CentOS Linux release 7.2.1511 (Core)

From /etc/*release* /etc/*version*
centos-release: CentOS Linux release 7.2.1511 (Core)
centos-release-upstream: Derived from Red Hat Enterprise Linux 7.2 (Source)
os-release:
  NAME="CentOS Linux"
  VERSION="7 (Core)"
  ID="centos"
  ID_LIKE="rhel fedora"
  VERSION_ID="7"
  PRETTY_NAME="CentOS Linux 7 (Core)"
  ANSI_COLOR="0;31"
  CPE_NAME="cpe:/o:centos:centos:7"
redhat-release: CentOS Linux release 7.2.1511 (Core)
system-release: CentOS Linux release 7.2.1511 (Core)
system-release-cpe: cpe:/o:centos:centos:7

uname -a:
Linux kn11.uits.indiana.edu 3.10.0-327.13.1.el7.xppsl_1.3.3.151.x86_64 #1 SMP
Fri Jun 10 15:04:35 UTC 2016 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Oct 13 14:15

SPEC is set to: /home/ljunj/SPEC/omp2012-1.1-run
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda3        ext4  713G  78G  599G  12% /


Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

(End of data from sysinfo program)
```

General Notes

BIOS settings:

Intel Simultaneous Multithreading (SMT): on
Intel Turbo Boost Technology (Turbo): off
Cluster Mode: quadrant

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Colfax International

(Test Sponsor: Indiana University)

Intel Xeon Phi 7210, 1.30GHz,

SMT off, Turbo off, flat (MCDRAM Preferred)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.19

OMP2012 license:3440A

Test sponsor: Indiana University

Tested by: Indiana University

Test date: Aug-2016

Hardware Availability: Aug-2016

Software Availability: Apr-2016

General Notes (Continued)

Memory Mode: flat

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Base Portability Flags

350.md: -free
357.bt331: -mcmodel=medium
363.swim: -mcmodel=medium
367.imagick: -std=c99

Base Optimization Flags

C benchmarks:

-O3 -ansi-alias -no-prec-div -qopenmp -ipo -xMIC-AVX512
-fp-model fast=2

C++ benchmarks:

-O3 -ansi-alias -no-prec-div -qopenmp -ipo -xMIC-AVX512
-fp-model fast=2

Fortran benchmarks:

-O3 -no-prec-div -qopenmp -ipo -xMIC-AVX512 -fp-model fast=2

The flags files that were used to format this result can be browsed at

<http://www.spec.org/omp2012/flags/Intel-ic16.0-linux64.html>

<http://www.spec.org/omp2012/flags/colfax-knl.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/omp2012/flags/Intel-ic16.0-linux64.xml>

<http://www.spec.org/omp2012/flags/colfax-knl.xml>



SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Colfax International

(Test Sponsor: Indiana University)

Intel Xeon Phi 7210, 1.30GHz,
SMT off, Turbo off, flat (MCDRAM Preferred)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 7.19

OMP2012 license:3440A

Test date: Aug-2016

Test sponsor: Indiana University

Hardware Availability: Aug-2016

Tested by: Indiana University

Software Availability: Apr-2016

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.

Report generated on Wed Jan 11 12:09:32 2017 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 11 January 2017.