



SPEC® OMPG2012 Result

Copyright 2012-2023 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS X210c M7 (Intel Xeon Platinum 8490H)

SPECompG_peak2012 = 56.4

OMP2012 license:9019


Test date: Dec-2022

Hardware Availability: Mar-2023

Software Availability: Nov-2022

Test sponsor: Cisco Systems

Tested by: Cisco Systems



Hardware

CPU Name:	Intel Xeon Platinum 8490H
CPU Characteristics:	Intel Turbo Boost Technology up to 3.5 GHz
CPU MHz:	1900
CPU MHz Maximum:	3500
FPU:	Integrated
CPU(s) enabled:	120 cores, 2 chips, 60 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chip
Primary Cache:	32 KB I + 48 KB D on chip per core
Secondary Cache:	2 MB I+D on chip per core
L3 Cache:	112.5 MB I+D on chip per chip
Other Cache:	None
Memory:	1 TB (16 x 64 GB 2Rx4 PC5-4800B-R)
Disk Subsystem:	1 x 960 GB M.2 SSD
Other Hardware:	None
Base Threads Run:	240
Minimum Peak Threads:	120

Software

Operating System:	SUSE Linux Enterprise Server 15 SP4 5.14.21-150400.22-default
Compiler:	C/C++/Fortran: Version 2022.2.0.20221020 of Intel oneAPI DPC++/C++
Auto Parallel:	No
File System:	xfs
System State:	Multi-user, run level 3
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other Software:	None

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2023 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS X210c M7 (Intel Xeon Platinum 8490H)

SPECompG_peak2012 = 56.4

OMP2012 license:9019

Test date: Dec-2022

Test sponsor: Cisco Systems

Hardware Availability: Mar-2023

Tested by: Cisco Systems

Software Availability: Nov-2022

Maximum Peak Threads: 240

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	240	11.7	395	18.1	256	<u>17.1</u>	<u>271</u>	240	<u>18.3</u>	<u>253</u>	20.1	230	15.3	303
351.bwaves	240	102	44.2	<u>103</u>	<u>44.1</u>	103	44.0	120	102	44.3	<u>102</u>	<u>44.3</u>	102	44.6
352.nab	240	89.4	43.5	89.5	43.5	<u>89.4</u>	<u>43.5</u>	240	<u>89.5</u>	<u>43.5</u>	89.6	43.4	89.5	43.5
357.bt331	240	83.0	57.1	83.5	56.8	<u>83.3</u>	<u>56.9</u>	240	82.8	57.2	82.5	57.4	<u>82.8</u>	<u>57.3</u>
358.botsalgn	240	93.0	46.8	93.0	46.8	<u>93.0</u>	<u>46.8</u>	240	<u>93.1</u>	<u>46.7</u>	93.1	46.7	93.0	46.8
359.botsspar	240	170	30.9	169	31.1	<u>169</u>	<u>31.0</u>	240	<u>169</u>	<u>31.1</u>	169	31.1	169	31.0
360.ilbdc	240	104	34.3	<u>104</u>	<u>34.3</u>	104	34.4	240	<u>104</u>	<u>34.3</u>	104	34.3	104	34.3
362.fma3d	240	103	36.9	104	36.4	<u>104</u>	<u>36.6</u>	240	<u>103</u>	<u>36.9</u>	103	36.9	104	36.5
363.swim	240	124	36.6	123	36.8	<u>123</u>	<u>36.8</u>	120	123	36.9	<u>123</u>	<u>36.9</u>	123	36.9
367.imagick	240	<u>82.6</u>	<u>85.1</u>	82.4	85.3	82.9	84.8	240	<u>83.2</u>	<u>84.5</u>	84.1	83.6	82.6	85.1
370.mgrid331	240	<u>151</u>	<u>29.4</u>	151	29.4	151	29.4	120	137	32.3	137	32.3	<u>137</u>	<u>32.3</u>
371.applu331	240	56.8	107	<u>56.7</u>	<u>107</u>	56.7	107	240	56.8	107	56.7	107	<u>56.7</u>	<u>107</u>
372.smithwa	240	47.0	114	<u>47.3</u>	<u>113</u>	47.3	113	240	47.1	114	<u>47.2</u>	<u>114</u>	47.6	113
376.kdtree	240	85.9	52.4	<u>85.9</u>	<u>52.4</u>	86.0	52.3	240	<u>85.9</u>	<u>52.4</u>	85.8	52.4	<u>85.9</u>	<u>52.4</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

Sysinfo program /home/omp2012/Docs/sysinfo
 Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
 running on x210m7-Arthur Tue Dec 13 06:30:24 2022

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) Platinum 8490H
  2 "physical id"s (chips)
  240 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 60
siblings : 120
physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
  22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
  47 48 49 50 51 52 53 54 55 56 57 58 59
physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
  22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
  47 48 49 50 51 52 53 54 55 56 57 58 59
```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2023 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS X210c M7 (Intel Xeon Platinum 8490H)

SPECompG_peak2012 = 56.4

SPECompG_base2012 = 56.2

OMP2012 license:9019

Test date: Dec-2022

Test sponsor: Cisco Systems

Hardware Availability: Mar-2023

Tested by: Cisco Systems

Software Availability: Nov-2022

Platform Notes (Continued)

```
cache size : 115200 KB

From /proc/meminfo
MemTotal:      1056457400 kB
HugePages_Total:      0
Hugepagesize:     2048 kB

From /etc/*release* /etc/*version*
os-release:
  NAME="SLES"
  VERSION="15-SP4"
  VERSION_ID="15.4"
  PRETTY_NAME="SUSE Linux Enterprise Server 15 SP4"
  ID="sles"
  ID_LIKE="suse"
  ANSI_COLOR="0;32"
  CPE_NAME="cpe:/o:suse:sles:15:sp4"

uname -a:
Linux x210m7-Arthur 5.14.21-150400.22-default #1 SMP PREEMPT_DYNAMIC Wed May
11 06:57:18 UTC 2022 (49db222) x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Dec 13 05:59

SPEC is set to: /home/omp2012
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda3        xfs   884G  194G  690G  22% /home
Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program
reads system data which is "intended to allow hardware to be accurately
determined", but the intent may not be met, as there are frequent changes to
hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Cisco Systems, Inc. X210M7.4.2.600.548.120122205 12/01/2022
Memory:
 16x 0xAD00 HMCG94MEBRA121N 64 GB 2 rank 4800 MT/s

(End of data from sysinfo program)
```

General Notes

```
=====
BIOS Setting:
  Sub NUMA Clustering set to Disabled
  ADDDC Sparing set to Disabled
  Processor C6 Report set to Enabled
  UPI Link Enablement 1
  UPI Link Power Management Enabled
  UPI Link Speed 16.0GT/S
```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2023 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS X210c M7 (Intel Xeon Platinum 8490H)

SPECompG_peak2012 = 56.4

OMP2012 license:9019

Test sponsor: Cisco Systems

Tested by: Cisco Systems

Test date: Dec-2022

Hardware Availability: Mar-2023

Software Availability: Nov-2022

General Notes (Continued)

```
=====
General OMP Library Settings:
ENV_KMP_LIBRARY = turnaround
ENV_KMP_BLOCKTIME = infinite
ENV_OMP_STACKSIZE = 8G
ENV_KMP_SCHEDULE = static
ENV_OMP_THREADS = 240
ENV_OMP_DYNAMIC = FALSE
=====
```

NA: The test sponsor attests, as of date of publication, the CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, the CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Spectre variant 2) is mitigated in the system as tested and documented.

```
=====
OS tuning:
```

Stack size set to unlimited using "ulimit -s unlimited"
Transparent Huge Pages enabled by default

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Base Portability Flags

```
350.md: -mcmodel=medium(*) -FR
351.bwaves: -mcmodel=medium(*)
352.nab: -mcmodel=medium(*)
357.bt331: -mcmodel=medium(-intel_ifort)(*) -mcmodel=medium(-intel_ifort)
358.botsalgn: -mcmodel=medium(*)
359.botsspar: -mcmodel=medium(*)
360.ilbdc: -mcmodel=medium(*)
362.fma3d: -mcmodel=medium(*)
363.swim: -mcmodel=medium(-intel_ifort)(*) -mcmodel=medium(-intel_ifort)
367.imagick: -mcmodel=medium(*) -std=c99
370.mgrid331: -mcmodel=medium(*)
371.applu331: -mcmodel=medium(*)
```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2023 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS X210c M7 (Intel Xeon Platinum 8490H)

SPECompG_peak2012 = 56.4

OMP2012 license:9019

Test date: Dec-2022

Hardware Availability: Mar-2023

Software Availability: Nov-2022

Test sponsor: Cisco Systems

Tested by: Cisco Systems

Base Portability Flags (Continued)

372.smithwa: -mcmodel=medium(*)
376.kdtree: -mcmodel=medium(*)

(*) Indicates a portability flag that was found in a non-portability variable.

Base Optimization Flags

C benchmarks:

-O3 -xCORE-AVX512 -ipol -qopenmp -qopt-zmm-usage=high -ansi-alias
-shared-intel -ffast-math -fstrict-enums -fstrict-vtable-pointers
-fvirtual-function-elimination

C++ benchmarks:

-O3 -xCORE-AVX512 -ipol -qopenmp -qopt-zmm-usage=high -ansi-alias
-shared-intel -ffast-math -fstrict-enums -fstrict-vtable-pointers

Fortran benchmarks:

-O3 -xCORE-AVX512 -ipol -qopenmp -qopt-zmm-usage=high -ansi-alias
-shared-intel -align array128byte -ffinite-math-only
-fno-omit-frame-pointer -m64

Peak Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

352.nab: -O3 -xCORE-AVX512 -ipol -qopenmp -qopt-zmm-usage=high
-ansi-alias -shared-intel -ffast-math -fstrict-enums
-fstrict-vtable-pointers -fvirtual-function-elimination

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2023 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS X210c M7 (Intel Xeon Platinum 8490H)

SPECompG_peak2012 = 56.4

OMP2012 license:9019

Test sponsor: Cisco Systems

Tested by: Cisco Systems

Test date: Dec-2022

Hardware Availability: Mar-2023

Software Availability: Nov-2022

Peak Optimization Flags (Continued)

352.nab (continued):
-fno-signed-zeros

358.botsalgn: -O3 -xCORE-AVX512 -ipol -qopenmp -qopt-zmm-usage=high
-ansi-alias -shared-intel -ffast-math -fstrict-enums
-fstrict-vtable-pointers -fvirtual-function-elimination

359.botsspar: Same as 358.botsalgn

367.imagick: Same as 358.botsalgn

372.smithwa: Same as 358.botsalgn

C++ benchmarks:

-O3 -xCORE-AVX512 -ipol -qopenmp -qopt-zmm-usage=high -ansi-alias
-shared-intel -ffast-math -fstrict-enums -fstrict-vtable-pointers

Fortran benchmarks:

350.md: -O3 -xCORE-AVX512 -ipol -qopenmp -qopt-zmm-usage=high
-ansi-alias -shared-intel -align array128byte
-ffinite-math-only -fno-omit-frame-pointer -m64

351.bwaves: Same as 350.md

357.bt331: -O3 -xCORE-AVX512 -ipol -qopenmp -qopt-zmm-usage=high
-ansi-alias -shared-intel -align array128byte
-ffinite-math-only -fno-omit-frame-pointer -m64 -norecursive

360.ilbdc: Same as 350.md

362.fma3d: Same as 350.md

363.swim: Same as 350.md

370.mgrid331: Same as 350.md

371.applu331: Same as 350.md

The flags file that was used to format this result can be browsed at

<http://www.spec.org/omp2012/flags/Cisco-ic2022.linux64-oneAPI.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/omp2012/flags/Cisco-ic2022.linux64-oneAPI.xml>



SPEC OMPG2012 Result

Copyright 2012-2023 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS X210c M7 (Intel Xeon Platinum 8490H)

SPECompG_peak2012 = 56.4

SPECompG_base2012 = 56.2

OMP2012 license:9019

Test sponsor: Cisco Systems

Tested by: Cisco Systems

Test date: Dec-2022

Hardware Availability: Mar-2023

Software Availability: Nov-2022

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.

Report generated on Wed Jan 11 14:04:07 2023 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 11 January 2023.