



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

HP Proliant BL460c blade Cluster Platform 3000BL

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

SPECmpIM_peak2007 = Not Run

SPECmpIM_base2007 = NC

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Ranks
104.milc
107.leslie3d
113.GemsFDTD
115.fds4
121.pop2
122.tachyon
126.lammps
127.wrf2
128.GAPgeoem
129.tera_tf
130.sjtu_3d
132.zeus_wp2
137.lu



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

HP Proliant BL460c blade Cluster Platform 3000BL

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

~~SPECmpIM_peak2007 = Not Run~~

SPECmpIM_base2007 = NC

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Results Tab

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	128	NC	NC	NC	NC	NC	NC									
107.leslie3d	128	NC	NC	NC	NC	NC	NC									
113.GemsFDTD	128	NC	NC	NC	NC	NC	NC									
115.fds4	128	NC	NC			NC	NC									
121.pop2	128	NC	NC	NC	NC	NC	NC									
122.tachyon	128	NC	NC	NC	NC	NC	NC									
126.lammps	128	NC	NC	NC	NC	NC	NC									
127.wrf2	128	NC	NC	NC	NC	NC	NC									
128.GAPgeomfem	128	NC	NC	NC	NC	NC	NC									
129.tera_tf	128	NC	NC	NC	NC	NC	NC									
130.socorro	128	NC	NC	NC	NC	NC	NC									
132.zeusmp2	128	NC	NC	NC	NC	NC	NC									
137.lu	128	NC	NC	NC	NC	NC	NC									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogenous
Compute Node:	HP XC Cluster
Interconnect:	DDR InfiniBand
File Server Node:	HP ProLiant DL380 G4 file server
Total Compute Nodes:	32
Total Chips:	64
Total Cores:	128
Total Threads:	128
Total Memory:	256 GB
Base Ranks Run:	128
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C 9.1.045
C++ Compiler:	Intel C++ 9.1.045
Fortran Compiler:	Intel Fortran 9.1.040
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	HP-MPI 2.2.5
Other MPI Info:	None
Pre-processors:	No
Other Software:	None



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

HP Proliant BL460c blade Cluster Platform 3000BL

~~SPECmpIM_peak2007 = Not Run~~

SPECmpIM_base2007 = NC

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Node Description: HP XC Cluster

Hardware

Number of nodes: 32
Uses of the node: compute
Vendor: Hewlett-Packard Company
Model: XC3000
CPU Name: Intel Xeon 5160
CPU(s) orderable: 1-2 chips
Chips enabled: 2
Cores enabled: 4
Cores per chip: 2
Threads per core: 1
CPU Characteristics: 1333 MHz FSB
CPU MHz: 3000
Primary Cache: 32 KB L1, 32 KB L2 on chip per core
Secondary Cache: 4 MB L3 on chip per chip
L3 Cache: None
Other Cache: None
Memory: 3 GB
Disk Subsystem: Ext 3
Other Hardware: None
Adapter: PCI-Express DDR InfiniBand HCA
Number of Adapters: 1
Slot Type: Mezzanine - PCIe x8
Data Transfer: Infiniband 4x DDR
Ports used: 1
Interconnect Type: InfiniBand

Software

Adapter: PCI-Express DDR InfiniBand HCA
Adapter Driver: Voltiare GridStack 3.5.5_25
Adapter Firmware: Hp 1.2
Operating System: Redhat 4 Update 4
Local File System: VXFS
Shared File System: NFS
System State: Multi User
Other Software: None



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

HP Proliant BL460c blade Cluster Platform 3000BL

~~SPECmpIM_peak2007 = Not Run~~

SPECmpIM_base2007 = NC

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Node Description: HP ProLiant DL380 G4 file server

Hardware

Number of nodes: 1
Uses of the node: file server
Vendor: Hewlett-Packard Company
Model: DL380 G4
CPU Name: Intel Xeon
CPU(s) orderable: 1-2 chips
Chips enabled: 2
Cores enabled: 2
Cores per chip: 1
Threads per core: 1
CPU Characteristics: None
CPU MHz: 3800
Primary Cache: 32 KB L1 32 KB L2 on chip per core
Secondary Cache: 2 MB L3 on chip per chip
L3 Cache: None
Other Cache: None
Memory: 3 GB
Disk Subsystem: SCSI
Other Hardware: None
Adapter: PCI-Express DDR InfiniBand HCA
Number of Adapters: 1
Slot Type: PCIe x4
Data Transfer: Infiniband 4x DDR
Ports Used: 1
Interconnect Type: InfiniBand

Software

Adapter: PCI-Express DDR InfiniBand HCA
Adapter Driver: Voltiare GridStack 3.5.5_25
Adapter Firmware: Hp 1.2
Operating System: Redhat 4 Update 4
Local File System: 2 x 146GB Ultra320 SCSI 10k RPM Disks RAID 0+1
Shared File System: N/A
System State: Multi User
Other Software: None



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

HP Proliant BL460c blade Cluster Platform 3000BL

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

~~SPECmpIM_peak2007 = Not run~~

SPECmpIM_base2007 = NC

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Interconnect Description: DDR InfiniBand

Hardware

Vendor: Voltaire
Model: ISR
Switch Model: HP 4X DDR IB Switch Module for HP BladeSystem C-Class
Number of Switches: 2
Number of Ports: 16
Data Rate: Infiniband 4x DDR
Firmware: 1.30
Switch Model: Voltaire 24 port External Switch for subnet management ISP 9024
Number of Switches: 1
Number of Ports: 24
Data Rate: Infiniband 4x DDR
Firmware: 0.8.6
Topology: two levels, 1 for subnet manager, and 1 for leaf.
Primary Use: MPI and Network system traffic

Software

General Notes

Tested in 2007 on XC3000 cluster.

measure load mpi

```
./.ashrc
./opt/intel/fc/9.1.040/bin/ifortvars.sh
./opt/intel/cc/9.1.045/bin/iccvars.sh
```

```
runspec -c linux_mmd_intel medium --reportable --ranks=NN --define CMD_PREFIX= --define MPIRUN_OPTIONS= --flagsurl=hpmppi-intel.xml -o cfg.txt,html,check
cluster launch performed via slurm's srun
submit= \$MPI_ROOT/bin/mpirun -srun $command
```



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

HP Proliant BL460c blade Cluster Platform 3000BL

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

~~SPECmpIM_peak2007 = Not Run~~

SPECmpIM_base2007 = NC

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Base Compiler Invocation

C benchmarks:

mpicc -mpicc icc

C++ benchmarks:

126.lammps: mpicC -mpicxx cpc

Fortran benchmarks:

107.leslie3d: mpif90 -mpif90 ifort

113.GemsFDTD: mpif90 -mpif90 ifort

115.fds4: mpif90 -mpif90 ifort

129.tera_tf: mpif90 -mpif90 ifort

132.zeusmp2: mpif90 -mpif90 ifort

137.lu: mpif90 -mpif90 ifort

Benchmarks using both Fortran and C (except as noted below):

mpicc -mpicc icc mpif90 -mpif90 ifort

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG

127.wrf2: -DSPEC_MPI_LINUX -DSPEC_MPI_CASE_FLAG



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

HP Proliant BL460c blade Cluster Platform 3000BL

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

~~SPECmpIM_peak2007 = Not Run~~

SPECmpIM_base2007 = NC

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

Base Optimization Flags

C benchmarks:

-O3 -no-prec-div -ftz -fno-alias -xT

C++ benchmarks:

126.lammps: -O3 -no-prec-div -ftz -fno-alias -xT

Fortran benchmarks:

107.leslie3d: -O3 -no-prec-div -ftz -fno-alias -xT

113.GemsFDTD: -O3 -no-prec-div -ftz -fno-alias -xT

115.fds4: -O3 -no-prec-div -ftz -fno-alias -xT

129.tera_tf: -O3 -no-prec-div -ftz -fno-alias -xT

132.zeusmp2: -O3 -no-prec-div -ftz -fno-alias -xT

137.lu: -O3 -no-prec-div -ftz -fno-alias -xT

Benchmarks using both Fortran and C:

111.pop1: -O3 -no-prec-div -ftz -fno-alias -xT

127.wrf2: Same as 121.pop2

128.GAPgmem: Same as 121.pop2

130.socorro: Same as 121.pop2



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Hewlett Packard Company

HP Proliant BL460c blade Cluster Platform 3000BL

MPI2007 license: 0001

Test sponsor: Hewlett-Packard Company

Tested by: HPCD

SPECmpIM_peak2007 = Not run

SPECmpIM_base2007 = NC

Test date: May-2007

Hardware Availability: May-2007

Software Availability: May-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement results could not be produced because of system access limitations.

The flags file that was used to format this result can be browsed at

http://www.spec.org/mpi2007/flags/MPI2007_flags.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/mpi2007/flags/MPI2007_flags.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v59.

Report generated on Tue Jul 22 13:32:38 2014 by SPEC MPI2007 PS/PDF formatter v1463.

Originally published on 16 July 2007.