



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER HPC2500 (1.3GHz)

SPECompMpeak2001 = --
SPECompMbase2001 = 30561

SPEC license #HPG0003 | Tested by: Fujitsu Limited | Test site: Numazu, Japan | Test date: May-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	30000 60000 90000		
310.wupwise_m	6000	125	48046			[Bar chart showing peak ratio]		
312.swim_m	6000	141	42553			[Bar chart showing peak ratio]		
314.mgrid_m	7300	195	37396			[Bar chart showing peak ratio]		
316.aplu_m	4000	51.2	78199			[Bar chart showing peak ratio]		
318.galgel_m	5100	308	16570			[Bar chart showing peak ratio]		
320.earthquake_m	2600	239	10867			[Bar chart showing peak ratio]		
324.apsi_m	3400	76.0	44757			[Bar chart showing peak ratio]		
326.gafort_m	8700	180	48361			[Bar chart showing peak ratio]		
328.fma3d_m	4600	190	24198			[Bar chart showing peak ratio]		
330.art_m	6400	261	24558			[Bar chart showing peak ratio]		
332.ammp_m	7000	446	15683			[Bar chart showing peak ratio]		

Hardware

CPU: SPARC64 V
 CPU MHz: 1299
 FPU: Integrated
 CPU(s) enabled: 128
 CPU(s) orderable: 8 to 128
 Primary Cache: 128KBI+128KBD on chip
 Secondary Cache: 2MB(I+D) on chip, per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 512GB
 Disk Subsystem: 1 x 36 GB Ultra SCSI
 Other Hardware: None

Software

OpenMP Threads: 96
 Parallel: OpenMP
 Operating System: Solaris 8
 Fujitsu Parallelnavi 2.2 (NQS etc)
 Compiler: Fujitsu Parallelnavi 2.2 (C & F90)
 File System: ufs
 System State: Multi-user

Notes/Tuning Information

Baseline flags:

C: -KOMP,fast_GP2=2,V9,largepage=2,hardbarrier -x-
 F90: -KOMP,fast_GP2=2,V9,largepage=2,hardbarrier,prefetch_line=4 -Nautoobjstack

Portability Flags:

318.galgel_m: -Am -Fixed -w
 328.fma3d_m: -Am

Extra Flags:

330.art_m: -DINTS_PER_CACHELINE=16 -DDBLS_PER_CACHELINE=8

System tunables:

```
/etc/system:
set shmsys:shminfo_shmmax=268435456
set shmsys:shminfo_shmmni=2048
set shmsys:shminfo_shmseg=2048
set autoup=4800
set memscrub_period_sec=345600
/etc/opt/FJSVpnm/lpg.conf:
JOB=408G,SHMSEGSIZE=256M
/etc/opt/FJSVpnm/cpursc.conf:
CPU_USE=0-3:0-3
```



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER HPC2500 (1.3GHz)

SPECompMpeak2001 = --
SPECompMbase2001 = 30561

SPEC license #HPG0003 | Tested by: Fujitsu Limited | Test site: Numazu, Japan | Test date: May-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

NQS:

```
Per-process data size limit = UNLIMITED
Per-process permanent file size limit = UNLIMITED
Per-process memory size limit = 40 gigabytes
Per-request memory size limit = 32 gigabytes
Per-process number of cpus limit = 124
Per-process stack size limit = 4 gigabytes
Per-process CPU time limit = 2147483646.000
Execution mode = SImplex
Jobclass = 0
```

Submitting the runspec to NQS:

Run the qsub command with the following sh script.

```
cd /spec/omp2001
. ./shrc
OMP_NUM_THREADS=96
export OMP_NUM_THREADS
runspec --config=Fujitsu --reportable medium
```