



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Java Workstation W2100z

SPECfp_rate2000 = 39.6
SPECfp_rate_base2000 = 35.2

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jul-2004 Hardware Avail: Jul-2004 Software Avail: Jul-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	97.5	38.1	2	73.7	50.4
171.swim	2	149	48.2	2	134	53.6
172.mgrid	2	129	32.4	2	110	38.0
173.applu	2	161	30.3	2	137	35.6
177.mesa	2	76.7	42.3	2	70.5	46.1
178.galgel	2	108	62.3	2	101	66.9
179.art	2	238	25.3	2	114	53.0
183.quake	2	97.8	30.8	2	95.7	31.5
187.facerec	2	84.8	52.0	2	84.8	52.0
188.amp	2	158	32.3	2	155	32.8
189.lucas	2	136	34.1	2	137	33.8
191.fma3d	2	141	34.7	2	141	34.7
200.sixtrack	2	148	17.2	2	148	17.2
301.apsi	2	173	34.8	2	170	35.4

Hardware

CPU: AMD Opteron (TM) 250
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB (I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x1GB, PC3200 CL3 DDR SDRAM ECC Registered
 Disk Subsystem: SCSI, 73GB, 10K RPM
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux WS 3 (AMD64)
 Compiler: PathScale EKO Compiler Suite, Release 1.1
 Red Hat gcc 3.5 ssa (from RHEL WS 3)
 PGI Fortran 5.2 (build 5.2-0E)
 AMD Core Math Library (Version 2.0) for AMD64
 File System: Linux/ext3
 System State: Multi-user, Run level 3

Notes/Tuning Information

A two-pass compilation method is used where indicated:

+PSFDO indicates PathScale feedback
 PASS1: -fb_create fbdata
 PASS2: -fb_opt fbdata
 +ACML is the AMD Core Math Library V2.0

Compilers:

C: pathcc (PathScale C) unless otherwise noted
 Fortran: pathf90 (PathScale f90) unless otherwise noted
 If other compilers are used, they are indicated as:
 gcc: Gnu C
 pgf90: PGI Fortran

Floating Point base tuning:

Fortran: pgf90 -fastsse -Mipa=fast -Msmart
 C: pathcc -Ofast -WOPT:mem_opnds=on +PSFDO



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Java Workstation W2100z

SPECfp_rate2000 = 39.6
SPECfp_rate_base2000 = 35.2

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jul-2004 Hardware Avail: Jul-2004 Software Avail: Jul-2004

Notes/Tuning Information (Continued)

Floating Point peak tuning:

```

168.wupwise: pgf90 -fastsse -Mipa=fast,inline -Msmart
171.swim: -Ofast -OPT:ro=3 -LNO:fusion=2:prefetch=2
172.mgrid: -O3 -OPT:Ofast
           -LNO:fusion=2:blocking=off:ou_max=5:sclrze=off:prefetch=2
           -OPT:unroll_times=8:unroll_size=256:ro=3
           -CG:gcm=off:cflow=off
173.applu: -O3 -ipa
           -LNO:fusion=2:interchange=OFF:blocking=OFF:ou_prod_max=10
           :ou_max=5:prefetch=2 -OPT:IEEE_arith=1:ro=3:unroll_size=0
           -TENV:X=4 -WOPT:mem_opnds=on:retype_expr=on:val=0 -CG:local_fwd_sched=on
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +PSFDO
178.galgel: pgf90 -fastsse -Mipa=fast -mp +ACML
           RM_SOURCES=lapak.f90 ONESTEP
179.art: -O3 -OPT:Ofast -fno-math-errno -m32 +PSFDO
183.earthquake: gcc -DSPEC_CPU2000_LP64 -O3 -funroll-all-loops -ffast-math
           -finline-limit=2000 ONESTEP
187.facerec: basepeak=true
188.ammp: -O3 -OPT:alias=disjoint:unroll_times=8:Ofast:ro=3
           -fno-math-errno -TENV:X=4 +PSFDO
189.lucas: pgf90 -fastsse -Mipa=fast,inline -Msmart
191.fma3d: basepeak=true
200.sixtrack: basepeak=true
301.apsi: -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0:blocking=off
           -IPA:linear=on:plimit=525

```

Portability:

178.galgel: -Mfixed

Notes:

BIOS build A5S1, default setting was used.