SPEC CINT95 Results

©Copyright 1995, Standard Performance Evaluation Corporation

Intel Corporation
XXpress Deskside (1110\133, 1MB L2)

SPECint95 = 4.14

SPECint_base95 = 4.14

SPEC license # 14 | Tested By: Intel | Test Date: Sep-95 | Hardware Avail: Jun-95 | Software Avail: Feb-96



Hardware/Software Configuration for:
XXpress Deskside (1110\133, 1MB L2)

Hardware

Model Name:	XXpress
CPU:	133MHz Pentium Processor
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	8KBI+8KBD
Secondary Cache:	1MB(I+D)
Other Cache:	None
Memory:	64MB (70ns fast page)
Disk Subsystem:	2x973MB Seagate ST 31250W
Other Hardware:	AIC 7870 PCI (onboard)

Software

Operating System:	UnixWare 2.0, SDK
Compiler:	Intel C Reference Compiler 2.2 Beta
File System:	ufs, vxfs (/tmp as 8MB /tmpfs)
System State:	Single user (root + killall)

Benchmark # and Name	Reference Time	Base Run Time	Base SPEC Ratio	Run Time	SPEC Ratio
099.go	4600	989	4.65	989	4.65
124.m88ksim	1900	450	4.22	450	4.22
126.gcc	1700	416	4.09	416	4.09
129.compress	1800	484	3.72	484	3.72
130.li	1900	411	4.62	411	4.62
132.ijpeg	2400	827	2.90	827	2.90
134.perl	1900	390	4.88	390	4.88
147.vortex	2700	606	4.46	606	4.46
SPECint_base95 (G. Mean)			4.14		
		SPECint95 (G. Mean)			4.14

Notes/Tuning Information

```
Base and non-base flags are the same and use Feedback Directed Optimization
Pass1: -tp p5 -ipo -prof_gen -ircdb_dir /tmp/IRCDB -dn
Pass2: -tp p5 -ipo -prof_use -ircdb_dir /tmp/IRCDB -dn
-ircdb_dir is a location flag and not an optimization flag
Portability: 124: -DSYSV -DLEHOST 130, 134, 147: -lm  132: -DSYSV  126: -lm -lc -L/usr/ucblib -lucb -lmalloc
Two processor module; 2nd processor disabled with UnixWare "psradm" command
```