SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

Digital Equipment Corp.
AlphaServer 2100A 5/375

SPECint_rate95 = 103

SPECint_rate_base95 = 88.4

SPEC license # 2 | Tested By: Digital NH | Test Date: Oct-96 | Hardware Avail: Oct-96 | Software Avail: Dec-96



Hardware/Software Configuration for:
AlphaServer 2100A 5/375

Hardware

Model Name:	AlphaServer 2100A 5/375
CPU:	374 MHz 21164
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	8KB(I)+8KB(D) on chip
Secondary Cache:	96KB on chip
Other Cache:	8MB
Memory:	128MB
Disk Subsystem:	2 x 2GB
Other Hardware:	Ethernet

Software

Operating System:	Digital UNIX V4.0A
Compiler:	DEC C V5.4-044 cc.alt/protect_headers.sh
File System:	UFS
System State:	Multi User

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	1	377	110	1	371	112
124.m88ksim	1	201	85.1	1	160	107
126.gcc	1	212	72.0	1	169	90.6
129.compress	1	190	85.2	1	156	104
130.li	1	237	72.1	1	186	92.1
132.ijpeg	1	204	106	1	208	104
134.perl	1	173	99.0	1	155	110
147.vortex	1	282	86.1	1	226	108
SPECint_rate_base95 (G. Mean)			88.4			
SPECint_rate95 (G. Mean)						103

Notes/Tuning Information

```
Compiler: cc.alt -migrate -std1   Base optimizations: -O5 -arch ev56 -non_shared -om
Portability flags: m88ksim: -DLEHOST   perl: -DI_TIME   vortex: -D__RISC_64__

Peak flags: all use -ifo -non_shared    go: -O4 -inline speed -om    m88ksim: -O5 -speculate all -inline speed
with feedback    gcc: -O5 -inline speed -arch ev56 -xtaso_short with feedback    compress: -O5 -tune ev5 -32data
-assume whole_program -arch ev56 -inline speed -om -lsys5    li: -O5 -inline speed -xtaso_short -speculate all
-lsys5 with feedback    ijpeg: -O5 -fast -unsigned -inline speed -arch ev56 -speculate all -lsys5 with feedback
perl: -O5 -inline speed -arch ev56 -lsys5 with feedback pass-2 only    vortex: -O5 -fast -inline speed with feedback

feedback: PASS1=-gen_feedback -g1
fdo_pre1=mv %binary% %exename%.orig;pixie -pids %exename%.orig -o %exename%
fdo_run1=%command%
fdo_post1=prof -pixie -feedback ../../src/%exename%.fb %exename%.orig %exename%.orig.Addrs %exename%.orig.Counts.*
PASS2=-feedback $(EXENAME).fb -r -ifo
fdo_pre2=mv %exename% %exename%.rr;ld -o %exename%fb %exename%.rr -lexc;pixie -pids %exename%fb -o %exename%
fdo_run2=%command%
fdo_post2=ld -om %exename%.rr -o %exename%.rrom -lexc;prof -pixie -merge %exename%fb.Counts %exename%fb %exename%fb.Addrs
%exename%fb.Counts.*;/usr/lib/cmplrs/cc/om -om_ireorg_feedback %exename%fb -o %binary% %exename%.rrom
gcc and li add -taso to feedback commands om and ld
```