SPEC CINT95 Results

©Copyright 1995, Standard Performance Evaluation Corporation

Hewlett-Packard
HP 9000 Model D370

SPECint95 = 10.4

SPECint_base95 = 9.43

SPEC license # 3	Tested By: HP Cupertino, CA	Test Date: Sep-95	Hardware Avail: Dec-96	Software Avail: Jul-96



Hardware/Software Configuration for:
HP 9000 Model D370

Hardware

Model Name:	HP 9000 Model D370
CPU:	160 MHz PA-RISC 8000
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	512KBI+512KBD off-chip
Secondary Cache:	None
Other Cache:	None
Memory:	768MB
Disk Subsystem:	1 Fast/Wide SCSI-2 1.0 GB
Other Hardware:	None

Software

Operating System:	HP-UX B.10.20
Compiler:	HP92453-01 A.10.32.03 HP C Compiler
File System:	HP-UX
System State:	Multi-user

Benchmark # and Name	Reference Time	Base Run Time	Base SPEC Ratio	Run Time	SPEC Ratio
099.go	4600	453	10.2	412	11.2
124.m88ksim	1900	187	10.2	163	11.7
126.gcc	1700	214	7.94	197	8.64
129.compress	1800	187	9.60	157	11.5
130.li	1900	183	10.4	175	10.9
132.ijpeg	2400	265	9.04	247	9.71
134.perl	1900	199	9.57	198	9.61
147.vortex	2700	304	8.87	253	10.7
SPECint_base95 (G. Mean)			9.43		
		SPECint95 (G. Mean)			10.4

Notes/Tuning Information

```
Portability Flags (base & peak): All: -Ae

Base Flags:
All: fastmem.o +Oall +I/+P
Linker Flag:  All: -Wl,-aarchive

Peak Flags:
All: +ESfic +ESlit +O4 +I/+P
099: +Oentrysched +Olibcalls +nofastaccess +Onolimit +Onoloop_unroll +Optrs_strongly_typed +Ostaticprediction
124: +Oaggressive +Onoparmsoverlap +Optrs_strongly_typed +Ostaticprediction
126: -DSPEC +Olibcalls +Onolimit +Ostaticprediction
129: +Odataprefetch +Olibcalls +Onofltacc +Onolimit +Optrs_strongly_typed +Owhole_program_mode
130: -lm +ESsfc +Oentrysched +Olibcalls +Onolimit +Onoloop_unroll +Onoptrs_to_globals +Owhole_program_mode
132: +ESsfc +Odataprefetch +Olibcalls +Onolimit +Optrs_strongly_typed +Owhole_program_mode
134: fastmem.o -lm +Olibcalls +Onolimit +Owhole_program_mode
147: fastmem.o -lm +Oentrysched +Olibcalls +Onolimit +Onoloop_unroll +Optrs_strongly_typed +Ostaticprediction
Linker Flag:  All: -Wl,-aarchive

Note: The +I/+P indicates the use of profile based optimization.
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 22110
(703) 331-0180
info@specbench.org
http://www.specbench.org