SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

UNISYS Corporation
ClearPath SMP6400 4-CPU(200MHz)

SPECint_rate95 = 291

SPECint_rate_base95 = 291

SPEC license # 15	Tested By: UNISYS	Test Date: Jan-97	Hardware Avail: Jan-97	Software Avail: Jan-97



Hardware/Software Configuration for:
ClearPath SMP6400 4-CPU(200MHz)

Hardware

Model Name:	ClearPath SMP6400 4-CPU(200MHz)
CPU:	Pentium Pro Processor 200MHz
FPU:	Integrated
Number of CPU(s):	4
Primary Cache:	8KBI + 8KBD
Secondary Cache:	512KB(I+D)
Other Cache:	None
Memory:	256MB
Disk Subsystem:	4GB SCSI-2
Other Hardware:	None

Software

Operating System:	SCO UnixWare 2.1
Compiler:	Intel C Reference Compiler V2.3.2
File System:	vxfs
System State:	Multi User

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	4	555	298	4	555	298
124.m88ksim	4	245	279	4	245	279
126.gcc	4	223	275	4	223	275
129.compress	4	297	218	4	297	218
130.li	4	214	320	4	214	320
132.ijpeg	4	294	293	4	294	293
134.perl	4	225	304	4	225	304
147.vortex	4	271	358	4	271	358
SPECint_rate_base95 (G. Mean)			291			
				SPECint_rate95 (G. Mean)		291

Notes/Tuning Information

```
Base and peak flags are same and use Feedback Directed Optimization
Pass1: -tp p6 -ipo -xi -prof_gen -ircdb_dir /pan/IRCDB
Pass2: -tp p6 -ipo -xi -prof_use -ircdb_dir /pan/IRCDB
-ircdb_dir is a location flag and not an optimization flag
Portibility : 124: -DSYSV -DLEHOST 130, 134, 147: -lm 132: -DSYSV 126: -lm -lc -L/usr/ucblib -lucb -lmalloc
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@specbench.org
http://www.specbench.org/

-- Prepared By: --