SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

Fujitsu teamserver G770i Dual

SPECint_rate95 = 189

SPECint_rate_base95 = 188

SPEC license # 42	Tested By: Fujitsu	Test Date: Apr-96	Hardware Avail: May-97	Software Avail: Jun-96



Hardware/Software Configuration for:
teamserver G770i Dual

Hardware

Model Name:	Fujitsu teamserver G770i Dual
CPU:	Pentium II 266MHz
FPU:	Integrated
Number of CPU(s):	2
Primary Cache:	16KBI+16KBD
Secondary Cache:	512KB(I+D)
Other Cache:	None
Memory:	128MB
Disk Subsystem:	2GB Fujitsu
Other Hardware:	None

Software

Operating System:	UnixWare 2.1.1
Compiler:	Intel C Reference Compiler V2.3.2
File System:	VXFS
System State:	Multi User

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	2	462	179	2	461	180
124.m88ksim	2	181	189	2	181	189
126.gcc	2	173	177	2	173	177
129.compress	2	245	132	2	231	140
130.li	2	166	206	2	165	207
132.ijpeg	2	227	190	2	227	190
134.perl	2	153	224	2	153	224
147.vortex	2	217	224	2	217	224
SPECint_rate_base95 (G. Mean)			188			
SPECint_rate95 (G. Mean)						189

Notes/Tuning Information

```
Base and peak flags are the same and use Feedback Directed Optimization
Pass1: -tp p6 -ipo  -prof_gen -ircdb_dir /proj/tmp/IRCDB
Pass2: -tp p6 -ipo  -prof_use -ircdb_dir /proj/tmp/IRCDB
-ircdb_dir is a location flag and not an optimization flag
Portability: 124: -DSYSV -DLEHOST 130, 134, 147: -lm  132: -DSYSV
-lm -lc -L/usr/ucblib -lucb -lmalloc
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@specbench.org
http://www.specbench.org/

-- Prepared By: --