SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

Sun Microsystems Ultra 450

SPECint_rate95 = 229

SPECint_rate_base95 = 186

SPEC license # 6	Tested By: Sun, Palo Alto	Test Date: Apr-98	Hardware Avail: Jul-98	Software Avail: Oct-98



Hardware/Software Configuration for: Ultra 450

Hardware

Model Name:	Ultra 450
CPU:	296 MHz UltraSPARC-II
FPU:	Integrated
Number of CPU(s):	2
Primary Cache:	16KBI+16KBD on chip
Secondary Cache:	2MB(I+D) off chip
Other Cache:	None
Memory:	512MB
Disk Subsystem:	2 x 4.0GB
Other Hardware:	Fast Ethernet System clock frequency: 99 MHz

Software

Operating System:	Solaris 2.6 3/98
Compiler:	Sun C SC5.0 EFT1 (8/98)
File System:	UFS
System State:	Single User
Kernel Extensions:	consistent_coloring=1

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	2	392	211	2	390	212
124.m88ksim	2	183	187	2	135	254
126.gcc	2	157	194	2	145	211
129.compress	2	157	206	2	130	250
130.li	2	225	152	2	143	239
132.ijpeg	2	227	190	2	221	196
134.perl	2	199	172	2	130	264
147.vortex	2	268	181	2	227	214
SPECint_rate_base95 (G. Mean)			186			
			SPECint_rate95 (G. Mean)			229

Notes/Tuning Information

```
P1= -xprofile=collect:‘pwd‘/../feedback
P2= -xprofile=use:‘pwd‘/../feedback
Baseline: -fast -xO5 -xarch=v8plusa
Baseline: PASS1= ${P1}; PASS2= ${P2}
Peak: -fast -xO4 -xarch=v8plusa -xchip=ultra
099.go: -fast -xO4 -xarch=v8plus -xrestrict -xcrossfile -W2,-O4+ansi_alias+bopt
099.go: PASS1= ${P1}; PASS2= ${P2} ${ALIGN} -dn
124.m88ksim: -fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile -xrestrict -W2,-O4+cond_elim+pde,-ldstr,-Mt8500 -Wc,-Qiselect-sw_pf_tbl_th=20
124.m88ksim: PASS1= ${P1}; PASS2= ${P2} -dn
126.gcc: -fast -xO4 -xarch=v8plus -W2,-O4+ansi_alias+cond_elim
126.gcc: PASS1= ${P1}; PASS2= ${P2}
129.compress: -fast -xO5 -xsafe=mem -xarch=v8plus -xrestrict -W2,-O4+ansi_alias+pde -Wc,-Qms_pipe+unoovf
129.compress: PASS1= ${P1}; PASS2= ${P2} -dn
130.li: PASS1= -fast -xO4 -xarch=v8plus -xcrossfile ${P1}
130.li: PASS2= -fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile -W2,-O4+ansi_alias+cond_elim+pde,-Mt350,-whole,-crit ${P2} -dn
132.ijpeg: -fast -xO5 -xsafe=mem  -xarch=v8plus -W2,-O4+ansi_alias+cond_elim
132.ijpeg: PASS1= ${P1}; PASS2= ${P2} -dn
134.perl: -fast -xO4 ${CULTRA} -xcrossfile -W2,-ANSI_S,-Mp1,-O4+cond_elim -Wc,-Qiselect-sw_pf_tbl_th=30
134.perl: PASS1= ${P1}; PASS2= ${P2} -dn
147.vortex: PASS1= -fast -xO4 -xarch=v8plus -xcrossfile ${P1}
147.vortex: PASS2= -fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile ${P2} -W2,-O4+cond_elim,-Mt500,-Mr6000,-crit -dn
Portability: 124.m88ksim, 132.ijpeg: -DSYSV -Xc, 126.gcc: -Dalloca=__builtin_alloca -Xc
others: -Xc
Shell limits: # ulimit -n 1024  or % limit descriptors 1024
Config file: ultra450_int.cfg
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@specbench.org
http://www.specbench.org/

--

Prepared By: Gnana