SPEC SDM 1 Summary

057.sdet

Concurrent Workload	Throughput Scripts/Hr.
1	103.0
9	844.7
18	1533.1
27	1930.0
36	2121.2
72	2144.5
108	2069.8
144	2018.0

Amdahl Corp.
Sun SPARCcenter 2000 (12 CPUs)

Hardware

Model Number	Sun SPARCcenter 2000
CPU	50 MHz SuperSPARC
FPU	Integrated
Number Of CPUs	12
Primary Cache	20KBI+16KBD on chip
Secondary Cache	2MB(I+D) off chip
Other Cache	None
Memory	1536MB
Other Hardware	none

Software

O/S & Version	Amdahl A+ Ed. 1.1 for Solaris 2.4
Compiler	gcc 2.1.1
Other Software	None

System

File System	UFS
Tuning Param.	See Notes
System State	Multi-user

Disk Subsystem

Controller 1: SBus Fast Diff SCSI-2/Buffered Ethernet Card
Disk 37: OS, swap (one file system), /opt Disk 38: /usr, /var
Disk 39: swap (one file system), benchmark Disk 40: Unused
Controllers 2-7: SBus Diff/Fast/Wide Intelligent SCSI-2 HA
Controller 2: Disks 1-6, File systems 1-6 --- All 40 disks: Sun 2.1 GB
Controller 3: Disks 7-12, File systems 7-12
Controller 4: Disks 13-18, File systems 13-18
Controller 5: Disks 19-24, File systems 19-24
Controller 6: Disks 25-30, File sys. 25-30;Controller 7: Disks 31-36, File sys. 31-36

Availability:
Hardware: May-93
Software: Dec-94

License #: 37 | **Tested:** Nov-94 | **By:** Amdahl | **Of:** Santa Clara, CA



Tuning Parameters/Notes/Summary Of Changes:
tune_t_fsflushr = 1

© 1995 by Standard Performance Evaluation Corporation (ph:703-698-9604 ext. 325)