

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Compaq Computer Corp.: Alphaserver DS20 6/667
Zeus Ltd: Zeus 3.3.5

SPECweb99 = 1050

Test Date: Feb-2000
Tester: Compaq

Hardware Avail: Apr-2000 OS Avail: Apr-1999 HTTP Software Avail: Feb-2000 Sup. Software Avail: Apr-1999 SPEC license #: 2

Hardware

Vendor: Compaq Computer Corp.
Model: Alphaserver DS20 6/667
Processor: 667 MHz 21264A
Processors: 2 cores, 2 chips, 1 core/chip
Primary Cache: 64KB(I)+64KB(D) on chip
Secondary Cache: 8MB off chip
Other Cache: none
Memory: 2 GB
Disk Subsystem: 3x4GB(RZ1CF-CF), 3x9GB(RZ1DB-CS)
Disk Controllers: Integral FW SCSI
Other Hardware: 2 x ALTEON ACEswitch 180 GbE Switch

Software

Operating System: Compaq Tru64 UNIX V4.0F
File System: UFS and AdvFS
Other Software: none

HTTP Software

Vendor: Zeus Ltd
HTTP Software: Zeus 3.3.5
API: ISAPI
Server Cache: none
Log Mode: Common Log Format

Test Sponsor

Test Date: Feb-2000
Tested By: Compaq
SPEC License: 2

Network

of Controllers: 2
Network Controllers: 2 x DEGPA-SA
of Nets: 2
Type of Nets: Gigabit Ethernet
Network Speed: 1000Mbit
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 10
Model: Digital Personal WorkStation 600au
Processor: 600MHz 21164
of Processors: 1
Memory: 1GB
Network Controller: DEGPA-SA
Operating System: Compaq Tru64 UNIX V4.0F
Compiler: DEC C V5.9-005

Notes/Tuning Information

SUT Notes

Operating System Notes

OS Tuning parameters:
proc:
maxusers = 2048
max-proc-per-user = 0
max-threads-per-user = 1024
per-proc-data-size = 0x40000000000
max-per-proc-data-size = 0x40000000000
max-per-proc-address-space = 0x40000000000
per-proc-address-space = 0x40000000000
socket:
sominconn = 32765
somaxconn = 32765
umc = 1
inet:
ipqs = 10
tcbhashnum = 10
tcbhashsize = 8192
tcp_sendspace = 60000
tcp_recvspace = 60000
ipqmaxlen=2000
vm:
ubc-maxpercent = 60
vm-mapentries = 50000

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

vm-vpagemax = 131072
vm-maxvas = 0x40000000000

vfs:

name-cache-hash-size = 8192
namei-cache-valid-time = 8400

advfs:

AdvfsCacheMaxPercent = 25
AdvfsCacheHashSize = 32768

AdvfsPreallocAccess = 32768

net:

netisrthreads=2
netisrwakeupthreshold=192

HTTP Software Notes

Zeus 3.3.5 Tuning

runningsites/<host>: bindaddr text 16.45.205.151,16.49.209.151

global.cfg:

tuning!bind_any yes
tuning!cache_files 37097
tuning!cache_flush_interval 9000
tuning!cache_large_file 1048576
tuning!cache_max_bytes 0
tuning!cache_small_file 102
tuning!cache_stat_expire 86400
tuning!num_children 3
tuning!so_wbuff_size 1048576
tuning!softservers no
tuning!unique_bind no
tuning!use_poll no

Hardware Notes

Disk Configuration:

disk1: OS and swap (/ , /usr, swap)
disk2: URLroot (/www)
disk3 & disk4: file_set (/www/file_set) [AdvFS Domain]
disk5 & disk6: http logging (/log) [lsm stripeset]

Network Notes

Network Tuning: N/A

Client Notes

proc:

maxusers = 1024
max-proc-per-user = 0
max-threads-per-user = 1024

socket:

sominconn = 32765
somaxconn = 32765

inet:

ipport_userreserved = 65000
tcp_recvspace = 60000
ipqmaxlen=2000

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Client Notes (Continued)

tcbhashsize=8192