

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

IBM: pSeries 630 Model 6E4
Zeus Technology Ltd.: Zeus 4.2r1

SPECweb99_SSL =1988

Test Date: Feb-2003
Tester: IBM

Hardware Avail: Feb-2003 OS Avail: Nov-2002 HTTPS Software Avail: Mar-2003 Sup. Software Avail: Mar-2003 SPEC license #: 11

Hardware

Vendor: IBM
Model: pSeries 630 Model 6E4
Processor: 1450MHz POWER4+
Processors: 4 cores, 1 chip, 2 cores/chip, 1 chip/SCM
Primary Cache: 64KBI+32KBD (on chip) per core
Secondary Cache: 1536KB(I+D) unified (on chip) per chip
Other Cache: 8MB unified (off chip)/SCM, 2SCM in SUT
Memory: 32 GB
Disk Subsystem: 2x18.2GB (10KRPM) 16Bit SCSI Disk
16x18.2GB (10KRPM) SSA Disk
(fast-write enabled)
Disk Controllers: Wide/Ultra-2 SCSI I/O Controller
IBM SSA 160 SerialRAID Adapter
Other Hardware: 4 x Alteon ACESwitch 180

Software

Operating System: AIX 5L V5.2(64bit)
File System: JFS2
Other Software: None

HTTPS Software

Vendor: Zeus Technology Ltd.
HTTPS Software: Zeus 4.2r1
API: ISAPI
Server Cache: None
Log Mode: Binary CLF

Test Sponsor

Test Date: Feb-2003
Tested By: IBM
SPEC License: 11

Network

of Controllers: 4
Network Controllers: 4 IBM Gigabit Ethernet-SX PCI-X Adapter(14106802)
of Nets: 4
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/sec
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 8
Model: IBM eServer pSeries 640 Model B80
Processor: 375 MHz POWER3-II
of Processors: 4
Memory: 4GB
Network Controller: 1 Gigabit Ethernet-SX PCI Adapter (14100401)
Operating System: AIX 5.2
Compiler: IBM Cset++ Version 5.1

Notes/Tuning Information

SUT Notes

APAR IY35693 was applied to AIX 5L V5.2
bindintcpu [interrupt level] [cpu] (Interrupt affinity - bind 4 Ethernet interrupts to 4 cpu's(1 interrupt to 1 cpu))
bindprocessor [processor] [cpu] (Process affinity - bind 4 Zeus child processes to 4 CPU's(1 process to 1 cpu))
maxpgahead=64(the maximum number of pages to be read ahead,default=8)
minperm=5%(the point below which the page-stealer will steal file of computational pages,default=20%)
maxperm=95%(the point above which the page stealing algorithm steals only file page,default=80%)
4 different logs for 4 zeus instances (1 log per zeus instance)
Disk layout: 1 disk for OS, 1 disk for webserver, 14 disks striped for file_set, 2 disks web logfile)
Set Gigabit Ethernet driver attribute rxdesc_queue_sz=512 (set RX descriptor queue size, default=1024)
Set Gigabit Ethernet driver attribute rxbuf_pool_sz=512 (set Receive buffer pool size, default=1024)
Set Gigabit Ethernet driver attribute copy_bytes=256 (copy packet into contiguous buffer on transmit if this many or less bytes, default=2048)
no(network option) tuning:
no -o tcp_sendspace=65536(default socket send buffer size, default=16384)
no -o tcp_recvspace=65536(default socket receive buffer size, default=16384)
no -o somaxconn=10240(max listen backlog, default=1024)
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds, default=1)
no -o tcp_newreno=0 (disables the modification to TCP's Fast Recovery algorithm as described in RFC 2582, default=1)
no -o tcp_inpcb_hashtab_siz=128021 (increase TCP PCB hash table size, default=24499)
SCM stands for Single Chip Module

HTTP API Notes

Zeus PEPP-06 SPECweb99 toolkit used for dynamic content
post.log in /weblog directory instead of doc_root
./Configure --sendfile=no --locking=semop
Compiled with IBM VAC 5.0.1

For more
Information
Contact

SPEC

info@spec.org
http://www.spec.org

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTP API Notes (Continued)

CFLAGS = -q64 -qlargetype -O2 -qmaxmem=8192
LDFLAGS = -q64 -qlargetype -bnoentry -Wl -G -bexpall -bM:SRE -lc -lbsd

Client Notes

no (network option) tuning:
no -o delayack=3(delay ack for connection setup and shutdown,default=0)
no -o delayackports={443}(delay ack ports,default={ })
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds,default=1)
no -o tcp_sendspace=65536(default socket send buffer size, default=16384)
no -o tcp_recvspace=65536(default socket receive buffer size, default=16384)
AIX (thread-scheduling option) tuning:
AIXTHREAD_SCOPE=S (AIX pthread environment variable, set all threads have system based contention scope, {1:1}, default=P{8:1})
AIXTHREAD_SLPRATIO=1:1 (AIX pthread environment variable, controls the number of kernel threads that should be held in reserve for sleeping threads, default={12:1})
YIELDLOOPTIME=1000 (AIX pthread environment variable, controls the number of times to yield the processor before blocking on a busy lock, default=0)

Other Notes

Starts 4 unique instances of Zeus sharing a common docroot
Each Zeus child process was bound to the processor corresponding to its NIC
Zeus 4.2r1 global.cfg (one per instance)
tuning!bind_any no
tuning!cache_files 50021
tuning!cache_large_file 1048576
tuning!cache_small_file 4096
tuning!cache_stat_expire 180000
tuning!cache_flush_interval 180000
tuning!cache_max_bytes 0
tuning!num_children 1
tuning!keepalive yes
tuning!ssl_keepalive yes
tuning!ssl_diskcache no
tuning!ssl_sessioncache_size 1031
tuning!keepalive_timeout 300
tuning!keepalive_max -1
tuning!listen_queue_size 9216
tuning!cbuff_size 1048576
tuning!multiple_accept yes
tuning!max_connections 1031
tuning!sendfile no
tuning!so_rbuff_size 32768
tuning!softservers no
tuning!unique_bind yes
tuning!use_poll no
tuning!cache_cooling_time 0
tuning!modules!cgi!cleansize 0
tuning!modules!cgi!cbuff_size 921632
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
Zeus_Site_Configuration (one per instance):
modules!cgi!enabled yes
modules!isapi!enabled yes
bindaddr ip_addr1
Tuning Disclosure: IBM-20011019.txt
Dynamic API: IBM-20011019_2-API.tar.gz