SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard: HP Integrity rx1600
Zeus Technology Limited: Zeus 4.2r3

SPECweb99_SSL =1278

Test Date: Nov-2003
Tester: Hewlett-Packard Company

Hardware Avail:	Feb-2004	OS Avail:	Sep-2003	HTTPS Software Avail:	Jul-2003	Sup. Software Avail:	Sep-2003	SPEC license #:	3

Hardware

Vendor:	Hewlett-Packard
Model:	HP Integrity rx1600
Processor:	Low Voltage Intel Itanium 2 1.0 GHz
# Processors:	2 cores, 2 chips, 1 core/chip
Primary Cache:	16KBI+16KBD on chip
Secondary Cache:	256KB unified on chip
Other Cache:	1536KB unified on chip
Memory:	8GB (4x2GB)
Disk Subsystem:	1x36GB, 1x73GB (15K RPM)
Disk Controllers:	Ultra320 Wide LVD SCSI (internal)
Other Hardware:	HP ProCurve Switch 2724

Software

Operating System:	HP-UX 11i v2
File System:	See SUT Notes
Other Software:	B3901BA HP C/ANSI C

HTTPS Software

Vendor:	Zeus Technology Limited
HTTPS Software:	Zeus 4.2r3
API:	ISAPI
Server Cache:	None
Log Mode:	Binary Log Format

Test Sponsor

Test Date:	Nov-2003
Tested By:	Hewlett-Packard Company
SPEC License:	3

Network

# of Controllers:	2
Network Controllers:	HP A6825A
# of Nets:	2
Type of Nets:	Gigabit Ethernet
Network Speed:	1 Gb/s
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	6
Model:	HP Integrity rx2600
Processor:	Intel Itanium 2 1.0 GHz
# of Processors:	2
Memory:	6GB
Network Controller:	HP A6825A
Operating System:	HPUX 11i v1.6
Compiler:	B3901BA B.11.22 HP C/ANSI C

Notes/Tuning Information

SUT Notes

All file systems are HFS
1 (36GB) disk used for OS
1 (73GB) disk split into three logical volumes using LVM
lvol1 (21GB) mounted with behind option used for doc_root & post.log
lvol2 (24GB) mounted with read-only option used for the file_set
lvol3 (24GB) mounted with largefiles, behind options used for logs
File system containing logs is 64KB block size (def. 8KB) and 8KB fragments (def. 1KB)
Bound each zeus instance to the processor corresponding to its NIC
Processor binding is performed by: mpsched -c cpu# -p pid
Set page size attribute for zeus.web and zeus.cgi binaries
chatr +pd 64K +pi 64K zeus.cgi
chatr +pd 64M +pi 64M zeus.web

Operating System Notes

HP-UX Tunable Parameters:
dbc_max_pct=30 Max Buffer Cache Size as Percent of RAM (50)
dbc_min_pct=30 Min Buffer Cache Size as Percent of RAM (5)
fs_async=1 Enables write calls to return before write operation is complete Boolean (0)
maxfiles=3000 Soft File Limit per Process (60)
maxfiles_lim=3000 Hard File Limit per Process (1024)
nfile=6000 Max number of open files (790)
ninode=60000 Max number of inodes (444)
scsi_max_qdepth=64 Max number of concurrent requests to a SCSI device(8)
tcphashsz=16384 Relative Scaling Factor for TCP & IP Int. Tables(2048)
vps_ceiling=4096 Max System selected page size [KB] (16)

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

vps_pagesize=64 Default User page size [KB] (4)
vxfs_ifree_timelag=3600000 VxFS Free Inode minimum existence time (0)

HTTPS Software Notes

Zeus Global Parameters:
tuning!cache_files 356750
tuning!cache_max_bytes 0
tuning!cache_small_file 4096
tuning!cache_large_file 999999
tuning!cache_stat_expire 86400
tuning!cache_flush_interval 86400
tuning!listen_queue_size 1024
tuning!multiple_accept yes
tuning!so_rbuff_size 0
tuning!so_wbuff_size 1048576
tuning!cbuff_size 65536
tuning!keepalive yes
tuning!keepalive_timeout 1200
tuning!keepalive_max -1
tuning!timeout 600
tuning!unique_bind yes
tuning!bind_any no
tuning!sendfile no
tuning!ssl_keepalive yes
tuning!ssl_sessioncache_size 5011
tuning!ssl_sessioncache_expiry 120
tuning!ssl_diskcache no
tuning!modules!cgi!cbuff_size 1048576
tuning!modules!cgi!cleansize 0
tuning!softservers no
tuning!use_select yes
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!modules!isapi!enabled no
tuning!cache_cooling_time 0
tuning!maxaccept 2048
Zeus runningsite configuration:
modules!security!enabled yes
modules!cgi!enabled yes
modules!isapi!enabled yes

HTTP API Notes

Zeus PEPP Toolkit(0.8) used for SPECweb99_SSL dynamic content
./Configure --sendfile=no --checkconfig=yes --locking=semop --ssl=yes --64bit=yes
Compiled with HP C/ANSI C developer's Bundle (B3901BA)
CFLAGS=+Ofaster +DD64 +DSitanium2
LDFLAGS = +DSitanium2,+pd,64k,+pi,64k

Network Notes

Networking Tunable Parameters:
tcp_xmit_hiwater_def=2000000 Max unsent data triggers flow control(32768)
tcp_conn_request_max=2048 Max outstanding connection reqs (20)
socket_caching_tcp=4096 Size of the socket cache (512)

Gigabit Tunable Parameters:
send_max_bufs=128 Number of sending buffers consumed to trigger interrupt (16)

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Network Notes (Continued)

recv_max_bufs=128 Number of receiving buffers consumed to trigger interrupt (1)
send_coal_ticks=5000 Number of ticks to wait to trigger interrupt (0)
recv_coal_ticks=12000 Number of ticks to wait to trigger interrupt (0)

Client Notes

Client code generated with ./configure --enable-posix-threads
HP-UX Tunable Parameters:
max_thread_proc=800 Number of threads per process (64)
maxfiles=2048 Soft File Limit Per Process (60)
maxusers=256 Value of MAXUSERS macro (32)
ncallout=5000 Increase number of pending timeouts
nfile=4096 Max mumber of open files (790)
ninode=5000 Max Number of Open Inodes (444)
nkthread=8000 Maximum number of system-wide threads (499)

Other Notes

Tuning Disclosure: HP-20030626.txt
Dynamic API: HP-20020723.-API.tar.gz